View product details on medias

26.12.2024, 06:35:04 UTC

SCHAEFFLER



# ARCA-PUMP-BARREL-50-S

Drum pump

Drum pump for hobbocks

## Technical information

### Technical data

| | | |
|---|---|---|
| | 50 kg hobbock | Usage |
| | Hand valve or metering pistol grease gun | Features |
| | Pneumatic pump | Design |
| | G1/4 (internal thread) | Connector compressed air inlet |
| | G1/4 (external thread) | Connector grease outlet |
| | 30 mm | Suction pipe diameter |
| | 750 mm | Suction pipe length |
| | 420 bar | Operating pressure (at 6 bar pneumatic supply pressure) |
| | 3.5 bar | Pneumatic supply pressure, min. |
| | 8.5 bar | Pneumatic supply pressure, max. |
| | 70:1 | Pressure ratio |
| | 1,100 cm³/min | Delivery rate |
| | 150 l/min | Maximum air consumption |
| | NLGI 2 | Maximum consistency class |
| | +10 °C ... +40 °C | Grease temperature (NLGI 2) |
| | 76 dB | Sound pressure level |
| ≈m | 6.37 kg | Weight |

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all further information and guidelines for this product.For further information you can use the contact form on our website