



TEGERA® 48

Learn more

OUR THICKEST NITRILE GLOVE

An all-round classic chemical protection nitrile glove 0,6 mm/23,6 mil useful in several environments from household to manufacturing. Good grip due to diamonds structure and extra-long sleeve for protection. Unflocked. Latex-free for reduced risk of allergy.

CHARACTERISTICS

- High level of protection
- Durable
- Good grip

FUNCTIONS

- Extra long
- Waterproof
- Approved for handling foodstuffs
- Protection against chemicals
- Latex-free
- Oil and grease resistant
- Extra dense against dirt and particles

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Corrosive injuries, contact with dirt, contact with chemicals, contact with moisture, contact with damp, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Petro-chemical work, chemical work, chemical technology work, laboratory work, paint spraying work, paper industry work, decontamination, sanitation

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, pulp and paper, chemical, rubber and plastic, metal fabrication

TYPE OF WORK

Medium weight

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

SPECIFICATION

TYPE Chemical protection gloves
CATEGORY Cat. III
THICKNESS 0,60 mm
LENGTH 450 mm
INSIDE Unflocked
GRIP DESIGN Diamond grip pattern
COLOUR Green
PAIRS PER: BUNDLE/CARTON 6/36
AQL 0.65
DISPLAY TYPE Bag
DIPPING MATERIAL Nitrile

COMPLIANCE

CE 2777

EAC TP TC 019:2011

Information/UIS

EN ISO 374-1:2016/A1:2018 Type A AJKLOP

EN ISO 374-5:2016 Virus

EN 388:2016+A1:2018 4102X

EN ISO 21420:2020

FEATURES

Waterproof

Chemical protection

TEST ACCORDING TO EN ISO 374-1:2016

Tested chemical	A	J	K	L	O	P
Permeation level	4	6	6	4	6	6
Degradation %	56,1	16,3	-3,4	65,3	9,6	13,0

SIZE		ARTICLE NUMBER	EAN
8	M	48-8	7392626038745
9	L	48-9	7392626038752
10	XL	48-10	7392626038769
11	XXL	48-11	7392626038776

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.