PRODUCT DETAILS

**ARTICLE: 22052FR**

# WHEEL N 80X25/40 PLAIN BORE SWIVEL FORK M22 + BRAKE





## Wheel series N

Wheels with injected polyurethane coating 58 Sh.D on polyamide 6 center. Available with standard shielded or stainless steel sealed precision ball bearings; standard or stainless steel roller bearings; plain bore.
Plain bore wheel.

## Castor series M22

M22 series, Medium-light pressed steel fork assemblies; swivel version has double ball raceways. Zincplated.
Trailing foot brake - total stop.




## Technical data

| | | |
|---|---|---|
| Wheel diameter | D | 80 mm |
| Tyre width | E | 25,0 mm |
| Bore diameter | d | 12 mm |
| Weight article | | 0,670 kg |
| Hub width | L | 40 mm |
| Overall height | H | 106 mm |
| Top plate outer dimensions | AxB | 102x83 mm |
| Bolt hole spacing | axb | 76x55 mm |
| Bolt hole spacing | axb | 80x60 mm |
| Fixing bolt diameter | g | M8 |
| Offset | F | 33 mm |
| Fork width | U | 40 mm |
| Load Capacity | | 100 kg |

### Related Articles

Spare part wheel: 9064
Basic version: 22052
Version with thread-guards: 22052PF
Version with trailing brake and thread-guards: 22052FRPF

**GENERAL INFORMATION / RECOMMENDATIONS AND WARNINGS**
The cited text and the complete catalogue in their most up-dated versions are available in the OEM's website page www.lagspa.it/downloads. The dimensions, descriptions, specifications and illustrations herein are indicative and subject to variations without notice. The fact that products are illustrated herein does not necessarily imply they are available from stock nor does it place us under any obligation to supply them.
Tests carried out refer to the original products with original accessories: the replacement of one of the components with others of different manufacture might prevent the same results from being achieved and will automatically invalidate any guarantee. Please contact our technical service concerning any special application.