5.92.025.368/0000

LUMOTAST FK/25, female quick connector



fields of application

- Measurement-control-regulation
- Mechanical and system engineering
- Signalling systems

description

The female connector is equipped with insulation displacement connectors for contacting 4-pole cables.

The 4-pole female connector is perfectly matched to the RAFI ribbon cable. The insulation displacement connector makes contact with the wires when the strip parts are pressed together.

technical data

general	
Color	light gray
Operating temperature, min.	-65 °C
Operating temperature, max.	105 °C
Packaging unit	50 pcs.
net weight	0.7 g
MOQ order	50 pcs.
RoHS compliant	Yes
REACH compliant	Yes
mounting diameters	
Outside dimension, length	7 mm
Outside dimension, width	9.55 mm
Outside dimension, height	10.6 mm
electrical data	
Rated voltage, min.	0.02 V
Rated voltage, max.	25 V
Rated current, min.	0.0001 A
Rated current, max.	0.1 A

direct links

- RAFI eCatalog

The information in this data sheet only contains general descriptions and / or performance features, which may not apply precisely as described to the respective application, and which my change due to further product enhancements. The technical data, illustrations and other information about our products are the mere results of individual technical testing. These descriptions and other product features are only binding if they expressly agreed upon at the time of the conclusion of a binding contract. In all other cases, we reserve the right to make technical changes as well as changes of availability. Pictures and other graphic illustrations are approximations only. All product names may be trademarks or brand names of the RAFI Group or any other sub-supplier of RAFI. The use of such by any third parties for their own purposes may infringe the rights of the respective entity holding those rights.

RAFI GmbH & Co. KG

Ravensburger Str. 128-134
88276 Berg / Ravensburg
Germany
www.rafi-group.com,
info.headquarters@rafi-group.com