This document was generated on 03/12/2023

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 1200845183

Status: Active

Overview: Brad Ultra-Lock Connection System

Description: Ultra-Lock (M12) Receptacle, 4 Poles, M16x1.5 Mounting Threads, Male (Straight) to 24 AWG PVC Leads, 0.30m (11.81") Length



Series image - Reference only

Documents:

Drawing (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR6837

General

Product Family	Industrial Receptacles
Series	120084
IP Rating	IP69K
NEMA Rating	NEMA 6
Overview	Brad Ultra-Lock Connection System
Product Name	Ultra-Lock (M12)
Taxonomy	Circular Industrial Connectors
Type	Single Ended (pigtail)
UPC	78172538866

Physical

Coupling Type	External Thread
Gender	Male
Keyway	Single
Length	0.30m
Material - Component	Nickel-plated Brass
Mounting Thread Size	M16 x 1.5
Net Weight	26.761/g
Orientation	Straight
Panel Mount	Back
Poles	4
Temperature Range - Operating	-25° to +90°C
Wire Size AWG	24
Wire/Cable Type	UL 1569

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	60V

Material Info

Engineering Number	WR4W46E03C3003

Reference - Drawing Numbers

Sales Drawing	1200845183-000

EU ELV
Not Relevant

EU RoHS
Compliant with Exemption 6(c)

China RoHS

REACH SVHC
Contained per - D(2022)4187-DC (10 June 2022)
Lead

Halogen-Free Status
Not Low-Halogen

For more information, please visit Contact US

China ROHS	50 Image
ELV	Not Relevant
RoHS Phthalates	Not Contained
ZZCERT_CE - Declaration of Conformity	CER_4000410151_00_000.pdf
ZZCERT_UKCA - Declaration of Conformity	CER_4000410546_00_000.pdf

Search Parts in this Series
120084 Series

This document was generated on 03/12/2023

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION