DATASHEET - Z-BB/UL25/1P1MU+AUX/37

Phase busbar, 1-phase+HS, 25qmm, pin, 1m

Part no. **Z-BB/UL25/1P1MU+AUX/37**
171137

General specifications		
Product name		Eaton Moeller series busbar
Part no.		Z-BB/UL25/1P1MU+AUX/37
EAN		4015081676262
Product Length/Depth		974.6 millimetre
Product height		56.8 millimetre
Product width		19.3 millimetre
Product weight		0.66 kilogram
Compliances		RoHS conform
Product Tradename		None
Product Type		Busbar
Product Sub Type		None
Product Specification Details		
Accessory/spare part type		Busbar for miniature circuit breaker
Ambient operating temperature - max		100 °C
Ambient operating temperature - min		-5 °C
Application		Switchgear for industrial and advanced commercial applications
Color		Other
Cross section		25 mm^2
Electric connection type		Pin
Features		Can be cut to size Insulated
Functions		Busbar
Heat dissipation capacity		0 W
Heat dissipation per pole, current-dependent		0 W
Number of modular spacings		1
Number of phases		1
Number of poles		Single-pole
Pitch dimensions		26.4 mm
Rated conditional short-circuit current (Iq)		0 kA
Rated operational voltage (Ue) - max		1000 V
Rated short-time withstand current (Icw)		0 kA
Rated surge voltage		10 kV
Rated uninterrupted current (Iu)		100 A
Static heat dissipation, non-current-dependent		0 W
Suitable for		Devices with auxiliary switch
Suitable for number of devices		0
Type		Z-BB/UL Busbar
Used with		Z-BB/UL Busbar

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Phase busbar (EC000215)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Phase busbar (ecl@ss13-27-37-13-06 [ACN992016])

Number of phases		1
Number of poles		1
Suitable for number of devices		0
Module width	mm	26.4

Cross section		mm^2	25
Length		mm	974.6
Can be cut to size			Yes
Width in number of modular spacings			1
Rated permanent current Iu		A	100
Type of electric connection			Pin
Insulated			Yes
Rated surge voltage		kV	10
Conditioned rated short-circuit current Iq		kA	0
Max. rated operation voltage Ue		V	1000
Rated short-time withstand current Icw		kA	0
Suitable for devices with N-conductor			No
Suitable for devices with auxiliary switch			Yes
Colour			Other

© 04/2023 by Eaton Industries GmbH