PRODUCT-DETAILS

# VBC7-30-10-07

# VBC7-30-10-07 Mini Rev.Contactor 12VDC



## General Information

| | |
|---|---|
| Extended Product Type | VBC7-30-10-07 |
| Product ID | GJL1313901R0107 |
| EAN | 4013614264375 |
| Catalog Description | VBC7-30-10-07 Mini Rev.Contactor 12VDC |
| Long Description | The VBC7-30-10 mini reversing contactor is a compact 3 pole contactor with 1 auxiliary contact, screw terminals and normal mechanical interlock. They are ideally suited for applications where reliability is a must and space is at a premium. Mini reversing contactors are used in residential buldings, commercial buildings and industrial applications for the control of three-phase motor loads up to 5.5 kW (AC-3). Further features are the noiseless and hum-free coil, a switch position indication and the integrated possibility for rail or wall mounting. |

## Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85365080 |

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 1SBC100214C0201 |
| Instructions and Manuals | 2CDC102046M6801 |

| Dimension Diagram | GJL1200447F0001 |
|---|---|

## Dimensions

| | |
|---|---|
| Product Net Width | 96.5 mm |
| Product Net Height | 57.5 mm |
| Product Net Depth / Length | 46.5 mm |
| Product Net Weight | 0.355 kg |

## Technical

| | |
|---|---|
| Number of Poles | 3 |
| Rated Operational Voltage | Auxiliary Circuit 690 V AC<br>Auxiliary Circuit 250 V DC<br>Main Circuit 690 V AC<br>Main Circuit 220 V DC |
| Rated Frequency (f) | Main Circuit 60 Hz<br>Main Circuit 50 Hz<br>Main Circuit DC |
| Rated Impulse Withstand Voltage ($U_{imp}$) | Main Circuit 6 kV |
| Rated Insulation Voltage ($U_i$) | 690 V<br>acc. to UL/CSA 600 V |
| Number of Main Contacts NC | 0 |
| Number of Main Contacts NO | 3 |
| Rated Operational Current AC-1 ($I_e$) | (220 / 240 V) 40 °C 20 A<br>(220 / 240 V) 55 °C 16 A<br>(380 / 440 V) 40 °C 20 A<br>(380 / 440 V) 55 °C 16 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |
| Rated Operational Power AC-3 ($P_e$) | (230 V) Three Phase 3 kW<br>(400 V) Three Phase 5.5 kW<br>(500 V) Three Phase 5.5 kW<br>(690 V) Three Phase, NO 3 kW |
| Rated Short-time Withstand Current ($I_{cw}$) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 96 A |
| Number of Auxiliary Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 1 |
| Conventional Free-air Thermal Current ($I_{th}$) | Main Circuit 20 A |
| Rated Control Circuit Voltage ($U_c$) | 12 V DC |
| Coil Operating Limits | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x Uc (at θ ≤ 55 °C) |
| Degree of Protection | Main Circuit Terminals IP20 |
| Pollution Degree | 3 |
| Mechanical Durability | 10000000 cycle |
| Minimum Switching Capacity | Auxiliary Circuit 17 V<br>Auxiliary Circuit 5 mA |

| | |
|---|---|
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour<br>(AC-15) 600 cycles per hour<br>(AC-3) 600 cycles per hour<br>(DC-1) 600 cycles per hour<br>(DC-13) 600 cycles per hour<br>(DC-3) 600 cycles per hour |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible 1/2x 1 ... 2.5 mm²<br>Rigid 1/2x 1 ... 4 mm² |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible 1/2x 1 ... 2.5 mm²<br>Rigid 1/2x 1 ... 4 mm² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible with Insulated Ferrule 1/2x 1 ... 2.5 mm²<br>Flexible 1/2x 1 ... 2.5 mm²<br>Rigid 1/2x 1 ... 4 mm² |
| Wire Stripping Length | Auxiliary Circuit 9 mm<br>Main Circuit 9 mm |
| Tightening Torque | Control Circuit 0.8 ... 1.1 N·m<br>Main Circuit 0.8 ... 1.1 N·m |
| Mounting on DIN Rail | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Standards | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1 |

## Technical UL/CSA

| | |
|---|---|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC |
| Full Load Amps Motor Use | (115 V AC) Single Phase 13.8 A<br>(200 V AC) Three Phase 7.8 A<br>(220 ... 240 V AC) Three Phase 9.6 A<br>(230 V AC) Single Phase 10 A<br>(440 ... 480 V AC) Three Phase 7.6 A<br>(550 ... 600 V AC) Three Phase 6.1 A |
| Horsepower Rating UL/CSA | (115 V AC) Single Phase 0.75 Hp<br>(200 V AC) Three Phase 2 Hp<br>(220 ... 240 V AC) Three Phase 3 Hp<br>(230 V AC) Single Phase 1.5 Hp<br>(440 ... 480 V AC) Three Phase 5 Hp<br>(550 ... 600 V AC) Three Phase 5 Hp |
| General Use Rating UL/CSA | (600 V AC) 16 A |
| Connecting Capacity Main Circuit UL/CSA | Stranded 1/2x 22-10 AWG |
| Connecting Capacity Auxiliary Circuit UL/CSA | Stranded 1/2x 22-10 AWG |
| Tightening Torque UL/CSA | Auxiliary Circuit 7 in·lb<br>Control Circuit 7 in·lb<br>Main Circuit 7 in·lb |

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Operation -20 ... +55 °C<br>Storage -40 ... +80 °C |

| | |
|---|---|
| Maximum Operating Altitude Permissible | 2000 m |
| Resistance to Shock acc. to IEC 60068-2-27 | 11 ms Pulse 15g |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 5 ... 150 Hz |
| RoHS Status | Following EU Directive 2011/65/EU |

## Certificates and Declarations (Document Number)

| | |
|---|---|
| CB Certificate | 1SAA938000-2002 |
| CQC Certificate | CQC2003010304064033 |
| cULus Certificate | cUL_E191658 |
| Declaration of Conformity - CCC | 2020980304001854 |
| Declaration of Conformity - CE | 1SAD938517-0001 |
| Declaration of Conformity - UKCA | 1SAD938500-1001 |
| DNV GL Certificate | 1SAA938000-0306 |
| EAC Certificate | 1SAA920000-2702 |
| Environmental Information | 1SAC200068H0009 |
| Instructions and Manuals | 2CDC102046M6801 |
| KC Certificate | 1SAA938000-1501 |
| RMRS Certificate | 1SAA938000-0704 |
| RoHS Information | 1SAD938517-0001 |

## Container Information

| | |
|---|---|
| Package Level 1 Units | 5 piece |
| Package Level 1 Width | 115 mm |
| Package Level 1 Height | 54 mm |
| Package Level 1 Depth / Length | 280 mm |
| Package Level 1 Gross Weight | 1.845 kg |
| Package Level 1 EAN | 4013614419256 |

## Classifications

| | |
|---|---|
| Object Classification Code | Q |
| ETIM 4 | EC000066 - Magnet contactor, AC-switching |
| ETIM 5 | EC000010 - Starter combination |
| ETIM 6 | EC000010 - Combination of contactors |
| ETIM 7 | EC000010 - Combination of contactors |
| eClass | V11.0 : 27371009 |
| UNSPSC | 39121529 |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

