Specifications

Eaton 266842



Catalog Number: 266842

Eaton Moeller series NZM - Molded Case Circuit Breaker. Connection, on rear, 3p, 1 page, size 4

General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
266842

EAN
4015082668426

Product Length/Depth
45 mm

Product Height
63 mm

Product Width
135 mm

Product Weight
1.667 kg

Compliances
IEC
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM4, N4

Type

Accessory Connection on rear Terminal

Amperage Rating

1250 A

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM4

Drawings

eaton-circuit-breaker-connection-nzm-rear-connection-dimensions-004.eps

Installation instructions

IL01219017Z

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

DA-CS-nzm4_3p_xkr_o_u

DA-CD-nzm4_3p_xkr_o_u

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM4

Suitable for

Three-pole
Copper cable lugs
Aluminum cable lug

Number of poles

Three-pole

Terminal capacity (copper strip)

10 segments of 50 mm x 1 mm (2x)

Model

Other

Terminal capacity (stranded cable)

185 mm² (1x)
50 mm² - 185 mm² (4x)
95 mm² - 185 mm² (2x)

35 mm² - 185 mm² (4x)

120 mm² - 185 mm² (1x)

70 mm² - 185 mm² (2x)

Terminal capacity (copper busbar)

50 mm x 10 mm (2x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia