Specifications

Eaton C22G12S

Catalog Number: C22G12S

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 12 Amps, 80 kA Breaking capacity, class gG/gL, with striker, compatible with a CH22 Modular fuse holder



General specifications

Product Name
Eaton Bussmann series low voltage cylindrical fuse

Catalog Number
C22G12S

EAN
5027590495288

Product Length/Depth
58 mm

Product Height
22 mm

Product Width
22 mm

Product Weight
55.1 g

Compliances
RoHS Compliant
CE Marked

Certifications
IEC 60269

Powering Business Worldwide

Electrical data

Amperage Rating

12 A

Voltage rating

690 V

Voltage type

AC

Breaking capacity

80 kA

Utilization category

gG (cable protection/equipment protection)

Frequency rating - max

62 Hz

Compatible fuse holder

Suitable for

CH22 Modular fuse holder

Resources

Catalogs

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

CA134002EN

Declarations of conformity

CE C08G, C08M, etc cylindrical fuselinks

UKCA C08G, C08M, etc cylindrical fuselinks

Technical data sheets

720115 Cylindrical fuses

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia