PRODUCT-DETAILS

# AF38ZB-30-00K-22

## AF38ZB-30-00K-22 48-130V50/60HZ-DC Contactor



### General Information

| | |
|---|---|
| Extended Product Type | AF38ZB-30-00K-22 |
| Product ID | 1SBL296063R2200 |
| EAN | 3471523010420 |
| Catalog Description | AF38ZB-30-00K-22 48-130V50/60HZ-DC Contactor |
| Long Description | The AF38ZB-30-00K-22 is a 3 pole - 690 V IEC or 600 UL contactor with Push-in spring terminals, controlling motors up to 18.5 kW / 400 V AC (AC-3) or 25 hp / 480 V UL and switching power circuits up to 45 A (AC-1) or 50 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories. |

### Ordering

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85364900 |

© 2025 ABB. All rights reserved.

## Popular Downloads

| | |
|---|---|
| Data Sheet, Technical Information | 1SBC100220C0201 |
| Instructions and Manuals | 1SBC101054M6801 |
| Instructions and Manuals (Part 2) | 1SAC200017M0002 |
| CAD Dimensional Drawing | 2CDC001079B0201 |

## Dimensions

| | |
|---|---|
| Product Net Width | 45 mm |
| Product Net Depth / Length | 86 mm |
| Product Net Height | 92.3 mm |
| Product Net Weight | 0.33 kg |

## Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 0 |
| Number of Auxiliary Contacts NC | 0 |
| Number of Poles | 3P |
| Standards | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives. |
| Rated Operational Voltage | Main Circuit 690 V |
| Rated Frequency (f) | Control Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz |
| Conventional Free-air Thermal Current ($I_{th}$) | acc. to IEC 60947-4-1, Open Contactors Θ = 40 °C 50 A |
| Rated Operational Current AC-1 ($I_e$) | (690 V) 40 °C 50 A<br>(690 V) 60 °C 42 A<br>(690 V) 70 °C 37 A |
| Rated Operational Current AC-3 ($I_e$) | (415 V) 60 °C 38 A<br>(440 V) 60 °C 38 A<br>(500 V) 60 °C 33 A<br>(690 V) 60 °C 24 A<br>(380 / 400 V) 60 °C 38 A<br>(220 / 230 / 240 V) 60 °C 40 A |
| Rated Operational Current AC-3e ($I_e$) | (415 V) 60 °C 38 A<br>(440 V) 60 °C 38 A<br>(500 V) 60 °C 33 A<br>(690 V) 60 °C 24 A<br>(380 / 400 V) 60 °C 38 A<br>(220 / 230 / 240 V) 60 °C 40 A |
| Rated Operational Current DC-1 ($I_e$) | (110 V) 2 Poles in Series, 40 °C 50 A<br>(110 V) 2 Poles in Series, 60 °C 42 A<br>(110 V) 2 Poles in Series, 70 °C 37 A<br>(110 V) 3 Poles in Series, 40 °C 50 A<br>(110 V) 3 Poles in Series, 60 °C 42 A |

© 2025 ABB. All rights reserved.

| | |
|---|---|
| | (110 V) 3 Poles in Series, 70 °C 37 A<br>(220 V) 3 Poles in Series, 40 °C 50 A<br>(220 V) 3 Poles in Series, 60 °C 42 A<br>(220 V) 3 Poles in Series, 70 °C 37 A<br>(72 V) 1-Pole, 40 °C 50 A<br>(72 V) 1-Pole, 60 °C 42 A<br>(72 V) 1-Pole, 70 °C 37 A<br>(72 V) 2 Poles in Series, 40 °C 50 A<br>(72 V) 2 Poles in Series, 60 °C 42 A<br>(72 V) 2 Poles in Series, 70 °C 37 A<br>(72 V) 3 Poles in Series, 40 °C 50 A<br>(72 V) 3 Poles in Series, 60 °C 42 A<br>(72 V) 3 Poles in Series, 70 °C 37 A |
| Rated Operational Current DC-3 ($I_e$) | (110 V) 2 Poles in Series, 40 °C 50 A<br>(110 V) 2 Poles in Series, 60 °C 42 A<br>(110 V) 2 Poles in Series, 70 °C 37 A<br>(110 V) 3 Poles in Series, 40 °C 50 A<br>(110 V) 3 Poles in Series, 60 °C 42 A<br>(110 V) 3 Poles in Series, 70 °C 37 A<br>(220 V) 3 Poles in Series, 40 °C 50 A<br>(220 V) 3 Poles in Series, 60 °C 42 A<br>(220 V) 3 Poles in Series, 70 °C 37 A<br>(72 V) 1-Pole, 40 °C 50 A<br>(72 V) 1-Pole, 60 °C 42 A<br>(72 V) 1-Pole, 70 °C 37 A<br>(72 V) 2 Poles in Series, 40 °C 50 A<br>(72 V) 2 Poles in Series, 60 °C 42 A<br>(72 V) 2 Poles in Series, 70 °C 37 A<br>(72 V) 3 Poles in Series, 40 °C 50 A<br>(72 V) 3 Poles in Series, 60 °C 42 A<br>(72 V) 3 Poles in Series, 70 °C 37 A |
| Rated Operational Current DC-5 ($I_e$) | (110 V) 2 Poles in Series, 40 °C 50 A<br>(110 V) 2 Poles in Series, 60 °C 42 A<br>(110 V) 2 Poles in Series, 70 °C 37 A<br>(110 V) 3 Poles in Series, 40 °C 50 A<br>(110 V) 3 Poles in Series, 60 °C 42 A<br>(110 V) 3 Poles in Series, 70 °C 37 A<br>(220 V) 3 Poles in Series, 40 °C 25 A<br>(220 V) 3 Poles in Series, 60 °C 25 A<br>(220 V) 3 Poles in Series, 70 °C 25 A<br>(72 V) 1-Pole, 40 °C 25 A<br>(72 V) 1-Pole, 60 °C 25 A<br>(72 V) 1-Pole, 70 °C 25 A<br>(72 V) 2 Poles in Series, 40 °C 50 A<br>(72 V) 2 Poles in Series, 60 °C 42 A<br>(72 V) 2 Poles in Series, 70 °C 37 A<br>(72 V) 3 Poles in Series, 40 °C 50 A<br>(72 V) 3 Poles in Series, 60 °C 42 A<br>(72 V) 3 Poles in Series, 70 °C 37 A |
| Rated Operational Power AC-3 ($P_e$) | (415 V) 18.5 kW<br>(440 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 22 kW<br>(380 / 400 V) 18.5 kW<br>(220 / 230 / 240 V) 11 kW |
| Rated Operational Power AC-3e ($P_e$) | (415 V) 18.5 kW<br>(440 V) 22 kW<br>(500 V) 22 kW<br>(690 V) 22 kW<br>(380 / 400 V) 18.5 kW<br>(220 / 230 / 240 V) 11 kW |
| Rated Short-time Withstand Current Low Voltage ($I_{cw}$) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 350 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 50 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 150 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 700 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 225 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 440 V 500 A<br>cos phi=0.45 (cos phi=0.35 for Ie > 100 A) at 690 V 200 A |
| Rated Insulation Voltage | acc. to IEC 60947-4-1 690 V |

© 2025 ABB. All rights reserved.

| | |
|---|---|
| ($U_i$) | acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 6 kV |
| Maximum Electrical Switching Frequency | (AC-1) 600 cycles per hour<br>(AC-15) 0 cycles per hour<br>(AC-2 / AC-4) 150 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 0 cycles per hour |
| Maximum Mechanical Switching Frequency | 3600 cycles per hour |
| Rated Control Circuit Voltage ($U_c$) | 50 Hz 48 ... 130 V<br>60 Hz 48 ... 130 V<br>DC Operation 48 ... 130 V |
| Power Loss | at Rated Operating Conditions AC-1 per Pole 2.44 W<br>at Rated Operating Conditions AC-3 per Pole 1.41 W |
| Operate Time | Between Coil De-energization and NC Contact Closing 13 ... 98 ms<br>Between Coil De-energization and NO Contact Opening 11 ... 95 ms<br>Between Coil Energization and NC Contact Opening 38 ... 90 ms<br>Between Coil Energization and NO Contact Closing 40 ... 95 ms |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M4 Screws Placed Diagonally |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 1 ... 6 mm²<br>Flexible with Insulated Ferrule 1/2x 1 ... 6 mm²<br>Flexible 1/2x 1 ... 6 mm²<br>Rigid Solid 1/2x 1 ... 2.5 mm²<br>Rigid Stranded 1/2x 4 ... 10 mm² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.5 ... 2.5 mm²<br>Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm²<br>Flexible 1/2x 0.5 ... 2.5 mm²<br>Rigid 1/2x 1 ... 2.5 mm²<br>Rigid Solid 1/2x 1 ... 2.5 mm² |
| Wire Stripping Length | Auxiliary Circuit 0 mm<br>Control Circuit 10 mm<br>Main Circuit 14 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Terminal Type | Push-in Spring Terminals |
| Product Name | Block Contactor |

## Technical UL/CSA

| | |
|---|---|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| General Use Rating UL/CSA | (600 V AC) 45 A |
| Horsepower Rating UL/CSA | (120 V AC) Single Phase 2 hp<br>(200 ... 208 V AC) Three Phase 10 hp<br>(220 ... 240 V AC) Three Phase 10 hp<br>(240 V AC) Single Phase 5 hp<br>(440 ... 480 V AC) Three Phase 25 hp<br>(550 ... 600 V AC) Three Phase 30 hp |
| Connecting Capacity Main Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG<br>Rigid Stranded 1/2x 18-8 AWG |
| Connecting Capacity Control Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG |
| Full Load Amps Motor Use | (120 V AC) Single Phase 24 A<br>(200 ... 208 V AC) Three Phase 32.2 A<br>(220 ... 240 V AC) Three Phase 28 A<br>(240 V AC) Single Phase 28 A<br>(440 ... 480 V AC) Three Phase 34 A |

© 2025 ABB. All rights reserved.

(550 ... 600 V AC) Three Phase 32 A

## Environmental

| | |
|---|---|
| Ambient Air Temperature | Close to Contactor without Thermal O/L Relay -40 ... 70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand | Category B according to IEC 60947-1 Annex Q |
| Maximum Operating Altitude Permissible | Without Derating 3000 m |
| Resistance to Vibrations | 4g Closed Position & 2g Open position 5 ... 300 Hz |
| Shock and Vibration Withstand acc. to IEC 61373 | Category 1, Class B |
| Pollution Degree | 3 |

## Material Compliance

| | |
|---|---|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2021-006202 |
| RoHS Declaration | 2CMT2021-006277 |
| RoHS Information | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006525 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## ABB EcoSolutions

| | |
|---|---|
| End Of Life Disassembling Instructions | 1SBC101080M6801 |
| Environmental Product Declaration - EPD | 1SBD250584E4000 |
| Sustainable Material Content in Packaging (wt. %) | Recycled Cardboard - 86 % |
| Sustainable Material Content in Product (wt. %) | Recycled Metal - 28 % |

## Certificates and Declarations

| | |
|---|---|
| CB Certificate | CB_SE-116364 |
| CCC Certificate | CCC_2024010304656668 |
| CQC Certificate | CQC2010010304445623 |
| Declaration of Conformity - CCC | 2020980304001254 |
| Declaration of Conformity - CE | 1SBD250002U1000 |
| Declaration of Conformity - UKCA | 1SBD250033U1000 |
| UL Certificate | UL-US-2150887-5<br>UL-CA-2142658-5 |

© 2025 ABB. All rights reserved.

## Container Information

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 93 mm |
| Package Level 1 Depth / Length | 86 mm |
| Package Level 1 Height | 45 mm |
| Package Level 1 Gross Weight | 0.36 kg |
| Package Level 1 EAN | 3471523010420 |

## External Classifications and Standards

| Object Classification Code | Q |
|---|---|
| ETIM 7 | EC000066 - Power contactor, AC switching |
| ETIM 8 | EC000066 - Power contactor, AC switching |
| ETIM 9 | EC000066 - Power contactor, AC switching |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF38



© 2025 ABB. All rights reserved.