*Date: 22/04/2024*

# A52.100/S, 0...500°C, 160x8mm

## Bimetal Thermometer, Industrial Series

| | |
|---|---|
| Item number: | 3902897 |
| Quantity: | 1 pcs. |
| Order code: | A52.100-S-C1S-GD-C160GDZ-Z-ZZZ TD FZZVC-AZ1ZZZZZZZZZZ |
| Overview: | A52.100/S, 0...500°C, 160x8mm<br>Process connection: G 1/2 B<br>Neck: 30 mm<br>flat instrument glass<br>*WIKA* |
| Details: | Bimetal Thermometer, Industrial Series<br>Specifications according to data sheet: TM 52.01<br>Accuracy class: class 1 per EN 13190<br>Case: stainless steel<br>Stem material: stainless steel<br>Model: A52.100, nominal size 100, location of stem centre back<br>Connection design: standard, male thread<br>Scale range: 0 °C ... 500 °C<br>Process connection: G 1/2 B<br>Stem diameter: 8 mm<br>Insertion length L1: 160 mm<br>Neck: 30 mm<br>norm-mark on dial: *EN 13190*<br>accuracy class on dial: *Cl.1*<br>Bimetallic thermometer, for industrial applications A52L<br>Specifications according to data sheet: TM 52.01<br>Accuracy class: class 1 per EN 13190<br>Case: stainless steel<br>Stem material: stainless steel<br>Model: A52.100, nominal size 100, location of stem centre back<br>Connection design: standard, male thread<br>Scale range: 0 °C ... 500 °C<br>Process connection: G 1/2 B<br>Stem diameter: 8 mm<br>Insertion length L1: 160 mm<br>Neck: 30 mm<br>Window: flat instrument glass<br>Case: Stainless steel<br>Ingress protection: IP 43<br>Manufacturer logo: *WIKA*<br>Stem material: stainless steel |

*© 2024 - WIKA Instruments s.a.r.l.*