Rittal – The System.

Faster – better – everywhere.

CMC III CAN bus connection cable – DK 7030.090

Date : Apr 27, 2021

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

CMC III CAN bus connection cable – DK 7030.090

created: 27.04.2021 build on www.rittal.com/uk-en



Product description

Description:	For connecting the PU to the CAN bus sensors III, units III and control units III as a bus, also for cabling together. Because it is available in different lengths, the CMC III system can be adapted to various applications and built to a custom design.
Applications:	For connecting the CAN bus units. Information and power transfer of the individual CAN bus units.

Product description

Dimensions:	Length: 0.5 m
Operating temperature:	Operation (environment): +0 °C...+55 °C
Ambient humidity (non-condensing):	Operation (environment): 5 % - 95 %
Interfaces/connections:	Connector (type): RJ45 Connector (type): RJ45
Packs of:	1 pc(s).
Weight/pack:	0.03 kg
Copper weight (kg per piece):	0
EAN:	4028177659414
Customs tariff number:	85444290

ETIM 7.0:	EC000313
ETIM 6.0:	EC000313
eCl@ss 8.0/8.1:	27189253
eCl@ss 6.0/6.1:	27189253
Product description:	DK CMC III CAN bus connection cable, L: 0,5 m, type: RJ45

Approvals

Certificates:	NA