Date: 25/04/2023

PG23LT.100 10 bar G1/2B lower mount

Low Temperature Gauge

Item number:	48746626
Quantity:	1 pcs.
Order code:	PG23LT33-58-100-BG410Z-GD-LMZHCZZIZ-ZZZZZZZ 211D30ZY0 - IZZZZZZ12ZZZ
Overview:	PG23LT.100 10 bar G1/2B lower mount POLARgauge Case: stainless steel case Case filling fluid: Silicon oil class 1.0 Measuring System 316L Ingress protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -70 ... +60 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number
Details:	Low Temperature Gauge Bourdon Tube Pressure Gauge for extreme low ambient temperatures to -70°C Model PG23LT Measuring system: stainless steel Case filling: with Case: stainless steel case Unit of outer Scale: bar Measuring range: gauge pressure range Scale range: 0...10 bar Nominal size: 100 Process connection: G 1/2 B Window: laminated safety glass Ingress protection: IP 65 Accuracy class: class 1.0 Overpressure safe: standard Case surface: bare Material pressure element: Measuring System 316L Case filling fluid: Silicon oil M5 Permissible medium temperature: + 100 °C Permissible ambient temperature: -70 ... +60 °C Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA* Connection location: lower mount with Serial number POLARgauge

© 2023 - WIKA Instruments s.a.r.l.