*Date: 11/04/2023*

# TG54.063/4, DS, 0...200°C , L1=63 mmx8mm

## Model: TG54.063

| | |
|---|---|
| Item number: | 48759927 |
| Quantity: | 1 pcs. |
| Order code: | TG54.063DS-4-C1LZ-ND-C0063H1-ZAHAZZZ TO F-2ID-AZ1ZZZZZ2ZZZZ |
| Overview: | TG54.063/4, DS, 0...200°C , L1=63 mmx8mm<br>Process connection: 1/2 NPT<br>laminated safety glass<br>liquid damping<br>Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)<br>Stem material: 316SS<br>Ingress protection: IP 65<br>Permissible ambient temperature: -40 ... +70 °C<br>*WIKA*<br>with Serial number |
| Details: | Model: TG54.063<br>Specifications according to data sheet: TM 54.02<br>Accuracy class: class 1 per EN 13190<br>Nominal size: 063<br>Connection location: back mount, adjustable<br>Connection design: 4, compression fitting, sliding on stem<br>Process connection: 1/2 NPT<br>Scale range: 0 °C ... 200 °C<br>Stem diameter: 8 mm<br>Insertion length L1: 63 mm<br>Window: laminated safety glass<br>Damping: liquid damping<br>Stem material: 316SS<br>Explosion protection: ATEX<br>Ignition protection type: Ex h<br>Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X)<br>Ingress protection: IP 65<br>Permissible ambient temperature: -40 ... +70 °C<br>with Serial number<br>Manufacturer logo: *WIKA* |

*© 2023 - WIKA Instruments s.a.r.l.*