TECHNICAL SPECIFICATION

Pioneer™ 2m Twin Fall Arrest Lanyard

Pioneer™ 2m Twin Fall Arrest Lanyard / FAR0207



DESCRIPTION

The Pioneer™ fall arrest lanyards are made from the highest quality kernmantle rope and have aluminium connectors, allowing users to feel confident and secure whilst using them, whether moving around or climbing structures.

Complete with 1 aluminium karabiner and 2 aluminium scaffold hooks.

OPTIONS

Pioneer™ 2m Twin Fall Arrest Lanyard (FAR0207)

SAFETY STANDARDS

EN 355

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Fall Indicator
Yes

Material
Kernmantle Rope Lanyard Diameter 11mm With Black and Red Tracer In the Rope To Indicate The Degradation Of Material.

Sharp Edge
No

Protective Rope Sleeve
No

Delivered With
1 Quarter Turn Aluminium Connector. Gate Opening 21mm. Conforms to EN362 Class B. 2 Aluminium Scaffold Hooks. Gate Opening 60mm. Conforms To EN362 Class A/T

Length
2m

Shock Absorber
External

Rope Ends
Stitched And Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops.

Product Weight
1960g

DOWNLOADS

Image Pack (ZIP)
doc-far0207.pdf (PDF)

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.