Specifications

# Eaton 119032



## Catalog Number: 119032

Eaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear Enclosure. Copper band 400A, 5x24x1mm, black

### General specifications

**Product Name**
Eaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear Enclosure

**Catalog Number**
119032

**EAN**
4015081171590

**Product Length/Depth**
2000 mm

**Product Height**
5 mm

**Product Width**
24 mm

**Product Weight**
2.3 kg

**Compliances**
UL CSA09 (max. 105 °C)
UL 758
CE marking
EN 60439-1
EN 60439-3
RoHS conform

**Certifications**
North America (UL listed, certified by UL for use in Canada)
UL (Category Control Number AVLV2)
UL (File No. E248096)

Powering Business Worldwide

## Product specifications

### Used with

Appliance wiring material
Copper band isolated

### Special features

E-Cu laminated conductor, tin-plated
UL approved up to max. 600 V AC
Insulating material heat resistant up to +105 °C

### Type

General switchboard accessory

### Features

Self-extinguishing acc. UL 94 V0
Laminated

### Accessory/spare part type

Copper band insulated

### Voltage rating

1000 V AC, 1500 V DC

### Voltage rating (UL CSA 13)

Max. 600 V AC, 750 V DC

### Busbar thickness

9 mm

### Cross section

120 mm²

### Lamella thickness

1 mm

### Number of fuse holders (knife blade)

5

### Amperage rating

400 A

### Color

Black, similar to RAL 9005

### Dielectric strength

20 kV/mm

### Dimensions - band specification

## Resources

### Catalogs

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

eaton-panel-building-accessories-catalog-ca008008en-en-us.pdf

### Drawings

eaton-distribution-boards-xeffect-multi-layer-copper-band-3d-drawing.eps

5 mm x 24 mm x 1 mm

Rated operation current (Ie)

400 A

---

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia