Specifications

Eaton 256793



Catalog Number: 256793

Eaton Moeller® series M22 Carrier, +label, EN SERVICE

General specifications

Product Name
Eaton Moeller® series M22 Accessory Legend holder

Catalog Number
256793

EAN
4015082567934

Product Length/Depth
4 mm

Product Height
50 mm

Product Width
30 mm

Product Weight
0.002 kg

Certifications
UL/CSA certification not required

Catalog Notes
Complete

Powering Business Worldwide

Features & Functions

Color

Black

Design

Round

Inscription

" EN SERVICE "

RAL-number

9005

Shape

Rectangular

General

Degree of protection

IP66

Opening diameter

22 mm

Product category

Accessories

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

70 °C

Communication

Connection to SmartWire-DT

No

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Please enquire

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

Not applicable.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Resources

Catalogs

Flip catalog - Product Range Catalog - Command and indication

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

eaton-rmq-titan-brochure-br047004en-en-us.pdf

Declarations of conformity

DA-DC-00004135.pdf

DA-DC-00004157.pdf

Drawings

eaton-operating-mounting-m22-legend-holder-dimensions-002.eps

eaton-operating-mounting-m22-legend-holder-dimensions-003.eps

eaton-operating-actuation-m22-legend-holder-dimensions.eps

eaton-operating-label-m22-legend-holder-dimensions.eps

eaton-operating-mounting-m22-legend-holder-dimensions.eps

eCAD model

ETN.256793.edz

Installation instructions

IL04716002Z

Installation videos

RMQ Flat Design

mCAD model

DA-CS-tastenzusatzschild

DA-CD-tastenzusatzschild

Multimedia

MCI Multicolor Light Indicator M22 with SmartWire-DT

RMQ small E-Stop emergency-stop button

MCI MultiColor Light Indicator RMQ compact solution

easyE4 SmartWire-DT module with Remote Touch Display and RMQ multi color indicator

PEP Eco-passport

EATO-00050-V01.01-EN

Sales notes

eaton-rmq-mci-multi-color-light-indicator-flyer-fl047005en-en-us.pdf

eaton-control circuit-devices rmq-titan-fl144090en-en-us.pdf

eaton-rmq-flat-enclosure-flyer-fl047003en-en-us.pdf

eaton-rmq-small-e-stop-flyer-fl047006en-en-us.pdf

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia