Specifications

Eaton 150684



Catalog Number: 150684

Eaton Moeller® series DILM RC suppressor circuit, 48 - 130 AC V, For use with: DILM17 - DILM32, DILK12 - DILK25, DILL…, DILMP32 - DILMP45

General specifications

Product Name
Eaton Moeller® series DILM RC suppressor circuit

Catalog Number
150684

EAN
4015081474691

Product Length/Depth
43 mm

Product Height
25 mm

Product Width
9 mm

Product Weight
0.005 kg

Certifications
CSA Class No.: 3211-07
CSA-C22.2 No. 14-05
UL 508
UL Category Control No.: NKCR2, NKCR8
CSA File No.: 256465
CE
CSA
UL Recognized
IEC/EN 60947-4-1
UL File No.: E29184

Catalog Notes
With DC operated contactors and with DILM115 and DILM150 the suppressor is integrated.

Powering Business Worldwide

Features Functions

Functions

RC-element

General

Product category

Accessories

Used with

DILM32-XSPR130

Voltage type

AC

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

Ambient operating temperature - max

60 °C

Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min

48 V

Rated control supply voltage (Us) at AC, 50 Hz - max

130 V

Rated control supply voltage (Us) at AC, 60 Hz - min

48 V

Rated control supply voltage (Us) at AC, 60 Hz - max

130 V

Rated control supply voltage (Us) at DC - min

0 V

Rated control supply voltage (Us) at DC - max

0 V

Design verification

Equipment heat dissipation, current-dependent Pvid

0 W

Heat dissipation capacity Pdiss

0 W

Heat dissipation per pole, current-dependent Pvid

0 W

Rated operational current for specified heat dissipation (In)

0 A

Static heat dissipation, non-current-dependent Pvs

0 W

10.2.2 Corrosion resistance

Meets the product standard's requirements.

Resources

Catalogs

Product Range Catalog Switching and protecting motors

SmartWire-DT Catalog

eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf

Declarations of conformity

DA-DC-00004819.pdf

DA-DC-00004815.pdf

DA-DC-00004996.pdf

DA-DC-00004814.pdf

DA-DC-00004912.pdf

DA-DC-00004776.pdf

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

DA-DC-00004880.pdf

DA-DC-00004816.pdf

DA-DC-00004992.pdf

DA-DC-00004983.pdf

DA-DC-00004988.pdf

DA-DC-00004784.pdf

DA-DC-00004785.pdf

DA-DC-00005005.pdf

DA-DC-00004783.pdf

Drawings

eaton-contactors-dilm-accessory-dimensions-003.eps

eaton-contactors-dilm-accessory-3d-drawing-004.eps

eCAD model

ETN.150684.edz

Installation instructions

IL03407014Z2021_09.pdf

Installation videos

WIN-WIN with push-in technology

mCAD model

DA-CS-dil_m_xsp_a

DA-CD-dil_m_xsp_a

Wiring diagrams

eaton-timers-suppressor-dilm-accessory-wiring-diagram-002.eps

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia