Date: 12/04/2023

PCA2MA 0,1 … 2,5 bar 1/4 NPT-F , 1/2 -14 NPT-F

Compact pressure switch, flameproof Enclosure Ex d

Item number: 48801674

Quantity: 1 pcs.

Order code: PCA2MA-BANC-1ASZZZ1ZZ CZKW
B000030DZZZZZZZZ
F4-C5- - - - -

Overview:
PCA2MA 0,1 … 2,5 bar 1/4 NPT-F , 1/2 -14 NPT-F
Compact pressure switch, flameproof Enclosure Ex d PCA
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
0,1 … 2,5 bar, working range -1 … 30 bar, proof pressure 40 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 0.30 bar decreasing,

Approvals / Certificates
IECEx-ATEX Ex d

Details:
Compact pressure switch, flameproof Enclosure Ex d
Model PCA
Specifications according to data sheet: PV 33.31
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Inconel + O-Ring FPM
1xSPDT, silver contact
0,1 … 2,5 bar, working range -1 … 30 bar, proof pressure 40 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: with
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCA2MA 0,1 … 2,5 bar
1. set point: 0.30 bar decreasing,

© 2023 - WIKA Instruments s.a.r.l.

Date: 12/04/2023

Approvals / Certificates
IECEx-ATEX Ex d

© 2023 - WIKA Instruments s.a.r.l.