DATASHEET - M30C-FWRS-MS5-A1

Key-operated actuator, Flat Front, maintained, 2 positions, MS5, Key withdrawable: 0, Metal bezel

Powering Business Worldwide

Part no.	**M30C-FWRS-MS5-A1**
	187058
EL Number (Norway)	**4315705**

Product name	Eaton Moeller® series M30 Key-operated actuator
Part no.	M30C-FWRS-MS5-A1
EAN	4015081821211
Product Length/Depth	36 millimetre
Product height	67 millimetre
Product width	46 millimetre
Product weight	0.06 kilogram
Certifications	VDE 0660 IEC/EN 60947 CSA-C22.2 No. 14-05 CE marking CSA file No. 012528 GL UL 508 UL File No.: E29184 CSA Class No.: 3211-03 DNV IEC/EN 60947-5 CSA certified UL Category Control No.: NKCR UL Listed CSA-C22.2 No. 94-91
Product Tradename	M30
Product Type	Key-operated actuator
Product Sub Type	None
Catalog Notes	Key withdraw convertible with coding adapters M22-XC-... Not suitable for master key systems
Bezel color	Chrome
Bezel material	Metal
Design	Key operation lock mechanism Flat front
Fitted with:	Front ring
Functions	Stay-put/spring-return function, can be changed with coding parts M22-XC-Y
Key code	MS5
Accessories	1 key included with supplied equipment.
Degree of protection	NEMA 4X, 13
Degree of protection (front side)	IP66
Lifespan, mechanical	100,000 Operations
Opening diameter	30 mm
Operating frequency	100 Operations/h
Operating torque	0.5 N·m
Product category	RMQ-Titan
Size	Front dimensions: Ø 36 mm
Switching angle	60 °
Type	Key-operated button
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Ambient operating temperature - min	-25 °C

Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Connection to SmartWire-DT		With SWD-RMQ connections Yes
Actuator color		Black
Actuator function		Switching function latching Key withdrawable in position 0 Maintained
Actuator type		Key
Number of switch positions		2
Force for positive opening - min		0 N

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss10.0.1-27-37-12-13 [AKF031014])

Number of switch positions		2
Type of control element		Key
Suitable for illumination		No
Colour control element		Black
Colour indicator light cap		Other
Construction type lens		Round
Hole diameter	mm	30
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Metal
Colour front ring		Chrome
Degree of protection (IP), front side		IP66
Degree of protection (NEMA)		4X, 13

© 04/2023 by Eaton Industries GmbH