PRODUCT-DETAILS

PSTX142-600-70

PSTX142-600-70 Softstarter - 142 A - 208 ... 600 V AC



General Information

© 2024 ABB. All rights reserved.

Global Commercial Alias	PSTX142-600-70
Extended Product Type	PSTX142-600-70
Product ID	1SFA898110R7000
ABB Type Designation	PSTX142-600-70
EAN	7320500501467
Catalog Description	PSTX142-600-70 Softstarter - 142 A - 208 ... 600 V AC
Long Description	The softstarter PSTX142-600-70 has a rated maximum operational current of 142 A with an operating voltage span from 208...600 V AC. The rated control voltage is between 100...250 V AC at 50/60 Hz. PSTX features a three-phase control soft start and stop through a voltage or a torque ramp. It has built-in bypass for easy installation and energy saving. A RUN, TOR and Event signal is available from relay outputs in NO (normally open state). The PSTX has functions such as current limit, kickstart, analog output, EOL, motor heating and pump cleaning. PSTX also features features jog, braking, stand-still brake, diagnostics, sequence start and emergency/fire pump mode as standard.To interact with PSTX, it has a detachable full graphic display with IP66 and 4x outdoor rating. There are four ways to communicate with PSTX. It can be done by hardwire inputs Start/Stop/Reset of fault, and by three programmable digital inputs. Another popular option is the built-in Fieldbus communication Modbus RTU and incl optional ANYBUS modules with every major protocol such as for example Profinet, Profibus, Modbus TCP, Ethernet IP and others. Another way to communicate with PSTX is to use an external adaptor and a Fieldbus plug. PSTX is the complete alternative for any motor starting application. It's suitable for medium to large-sized three-phase motors with nominal currents from 30...1250 A inline connection or 52...2160 A inside delta connection. Typical applications are, for example, pumps, fans, compressors, and conveyors.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85371091

Popular Downloads

Data Sheet, Technical Information	1SFC132012C0201
Instructions and Manuals	1SFC132081M0201
CAD Dimensional Drawing	2CDC001079B0201
Wiring Diagram	N/A

Dimensions

Product Net Width	199 mm
Product Net Height	377 mm
Product Net Depth / Length	283 mm
Product Net Weight	7 kg

Technical

Rated Operational Voltage	208 ... 600 V AC
Rated Control Supply Voltage (U_S)	100 ... 250 V AC
Rated Control Circuit Voltage (U_C)	24 V DC
Rated Frequency (f)	50/60 Hz

© 2024 ABB. All rights reserved.

	Main Circuit 50 / 60 Hz
Rated Operational Power - In-Line Connection (Pe)	(230 V) 37 kW (400 V) 75 kW (500 V) 90 kW
Rated Operational Current - In-Line Connection (Ie)	142 A
Rated Operational Power - Inside Delta Connection	at 230 V 75 kW at 400 V 132 kW at 500 V 160 kW
Rated Operational Current - Inside Delta Connection	245 A
Service Factor Percentage	100 %
Overload Protection	Built-in electronic overload protection
Integrated Electronic Overload	Yes
Adjustable Rated Motor Current Ie	30 ... 100 %
Starting Capacity at Maximum Rated Current Ie	4xIe for 10s
Ramp Time	1 ... 120 second [unit of time]
Initial Voltage During Start	10 ... 99 %
Step Down Voltage Special Ramp	100 ... 10 %
Current Limit Function	1.5 ... 7.5 xIe
Switch for Inside Delta Connection	Yes
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	Yes
Overload Signal Relay	Yes
Analog Outputs	0…10 V, 0…20 mA, 4…20 mA
Signal Indication Ready to Start/Standby ON (LED)	Green
Signal Indication Running R (LED)	Green
Signal Indication Protection (LED)	Yellow
Signal Indication Fault (LED)	Red
Communication	Modbus-RTU; Modbus-TCP; Ethernet-IP; EtherCAT; DeviceNet; CANopen; Profibus; Profinet; BACnet-IP; BACnet-MSTP
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars
Connecting Capacity Main Circuit	Hole Diameter 8.5 mm
Connecting Capacity Control Circuit	Rigid 1 x 2.5 mm^2
Connecting Capacity Supply Circuit	Rigid 1 x 2.5 mm^2
Tightening Torque	Main Circuit 14 N·m
Product Main Type	PSTX142
Function	Auto phase sequence detection Automatic restart Current limit Current limit ramp

© 2024 ABB. All rights reserved.

	Dual current limit Dynamic brake Electricity metering Electronic overload Time-to-cool Emergency mode Event log Full voltage start Jog with slow speed, forward and reverse Keypad password Kick start Limp mode with two-phase motor control if one set of thyristors is shorted Motor heating Pre-start function Pump cleaning Real time clock Sequence start Soft start with torque control Soft start with voltage ramp Soft stop with torque control Soft stop with voltage ramp Stand still brake Start reverse (external contactors) Thyristor runtime measurement Torque limit Voltage sags detection
Protection Function	Bypass open protection; Current imbalance protection; Current underload protection; Dual overload (separate overload for start and run); Earth fault protection / ground fault protection; Electronic overload protection, EOL; Extension IO failure protection; Fieldbus failure protection; HMI failure protection; Locked rotor protection; Max number of starts/hour; Over voltage protection; Phase reversal protection; Power factor underload protection; PT-100 connection; PTC connection; Too long current limit protection; Too long start time protection; Under voltage protection; User defined protection; Voltage imbalance protection
Warning Details	Current imbalance warning; Current underload warning; Electronic overload Time-to-trip; EOL warning; Faulty fan warning; Locked rotor warning; Motor runtime limit warning; Over voltage warning; Phase loss warning (for standby); Power factor underload warning; Short circuit warning (for Limp mode); THD(U) - Total Harmonic Distortion warning; Thyristor overload warning (SCR); Under voltage warning; Voltage imbalance warning

Technical UL/CSA

Horsepower Rating UL/CSA	(200 ... 208 V AC) Three Phase 40 Hp (220 ... 240 V AC) Three Phase 50 Hp (440 ... 480 V AC) Three Phase 100 Hp (550 ... 600 V AC) Three Phase 125 Hp
Maximum Operating Voltage UL/CSA	Main Circuit 600 V
Tightening Torque UL/CSA	Main Circuit 123.9

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

© 2024 ABB. All rights reserved.

REACH Declaration	2CMT2022-006481
RoHS Information	2CMT2022-006500
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	26f21088-b8bb-4914-b092-1fc09456661d China (CN)
Simplified SCIP	0ab76afe-9586-406c-b1d9-3f72d29c6360 Netherlands (NL) 117db3bc-26f8-486b-9661-9213c47e0dce Germany (DE) 13efe971-0aef-4a3e-b200-9388f7b13699 Sweden (SE) 14290cdf-4981-4228-ac25-fbf6ff6bede1 Poland (PL) 2a18edcd-ab8d-49d6-9e8e-a36742111f1c Belgium (BE) 3833bc73-a767-402d-b8b2-abad0c0099a9 Norway (NO) 3ac3b2ef-d72e-4baa-a85b-7a6308c05cd5 France (FR) 3ce45bbe-7f17-4746-a062-621c143a1593 Belgium (BE) 45148e2f-b3ab-4084-a4ff-2d3992dff4e3 Greece (GR) 483327c0-4c3f-426a-8884-5793dc883e80 Germany (DE) 4895692a-8d27-4479-86bf-173e094805d8 Finland (FI) 693ca665-b359-42b9-8505-0a1d73f17bb1 Croatia (HR) 721706c8-8f98-4edd-93f6-85eb76f49408 Sweden (SE) 734b7456-6afc-4ba5-9eb1-e44eb712b188 Estonia (EE) 7c8972af-46d8-45d8-9928-ca11c959706a Bulgaria (BG) 84993a02-0bda-48c2-a072-0f582e778ff3 Hungary (HU) 9601f0fb-71c8-46d6-901c-b0c11e41b94c Germany (DE) 98705313-f7c3-4ad9-bc8e-c866590c7b4c Germany (DE) a46c12be-e940-4ade-9322-97a2ddebbaed Portugal (PT) a7d57835-a734-4c2d-9f77-81733f7491bf Hungary (HU) ced2cf36-a96f-4b81-ac85-517042ee7ef1 Germany (DE) d73af370-e733-4369-9550-2ae47c351b48 Poland (PL) d8506a36-85a5-4e05-9a69-9b4c090cc148 Spain (ES) e079558d-a47b-4f28-8edf-f04ab44fd258 France (FR) e7f3ccdd-9d79-4c97-84ad-b4c479119f1b Poland (PL) ef546eb4-0fda-49d8-947c-db988a7a5730 Czech Republic (CZ) f3952e38-6433-4473-9a54-aee6eac8f612 Denmark (DK)
Toxic Substances Control Act - TSCA	2CMT2023-006524
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CQC Certificate	CN: CQC2014010304744407 / SE: CQC2014010304724379
Declaration of Conformity - CCC	CN: 2020980304001092 / SE: 2020980304001485
Declaration of Conformity - CE	2CMT005209
DNV Certificate	TAE000087N

Container Information

Package Level 1 Width	263 mm
Package Level 1 Depth / Length	323 mm
Package Level 1 Height	454 mm
Package Level 1 Gross Weight	8.7 kg
Package Level 1 EAN	7320500501467
Package Level 1 Units	box 1 piece

Classifications

Object Classification Code	Q

© 2024 ABB. All rights reserved.

ETIM 7	EC000640 - Soft starter
ETIM 8	EC000640 - Soft starter
ETIM 9	EC000640 - Soft starter
eClass	V11.0 : 27370907
UNSPSC	39121521
IDEA Granular Category Code (IGCC)	4740 >> Soft starter

Categories

Drives → Softstarters → Softstarters → PSTX Softstarters → PSTX142

Low Voltage Products and Systems → Control Products → Softstarters → Softstarters → PSTX Softstarters → PSTX142





© 2024 ABB. All rights reserved.