PRODUCT-DETAILS

E6.2V 6300 Ekip Dip LSIG 3p WMP

E6.2V 6300 Ekip Dip LSIG 3p WMP



General Information

Extended Product Type	E6.2V 6300 Ekip Dip LSIG 3p WMP
Product ID	1SDA072653R1
EAN	8015644765033
Catalog Description	E6.2V 6300 Ekip Dip LSIG 3p WMP
Long Description	MOVING PART FOR C.BREAKER SACE EMAX2 E6.2V 6300 THREE-POLE WITH SOLID-STATE RELEASE IN AC EKIP/DIP-LSIG R 6300 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

Ordering

EAN	8015644765033
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090
Order Code US and Canada	Z6VYETAC000A000000XX

Dimensions

Product Net Width	803 mm
Product Net Height	425 mm
Product Net Depth / Length	383 mm
Product Net Weight	120 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	1000 mm
Package Level 1 Gross Weight	129 kg
Package Level 1 EAN	8015644765033

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Additional Information

Current Type	AC
Electrical Durability	Ue =< 440 V 2000 cycle Ue = 500 ... 690 V 2000 cycle 10 cycles per hour
Mechanical Durability	12000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	1550 W
Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Current (I_n)	6300 A
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 150 kA (230 V AC) 150 kA (380 V AC) 150 kA (400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 130 kA (660 V AC) 100 kA (690 V AC) 100 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 100 kA for 3 s 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 130 kA (525 V AC) 130 kA (690 V AC) 100 kA
Rated Uninterrupted Current (I_u)	6300 A
Release	Ekip Dip LSIG
Release Type	EL

Short-Circuit Performance Level	V
Standards	IEC
Sub-type	E6.2
Version	W

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5544
Environmental Information	9AKK10103A1038
Instructions and Manuals	1SDH001000R0002
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Classifications

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2

