CAT. N° 0 266 33



ISOLATING SWITCH - DPX-IS 250 WITH RELEASE - 3P - 250 A - FRONT HANDLE

Pack (number of units)	1
Volume (dm³)	6
Weight (g)	2 894,00

Product characteristics

DPX-IS with release

- Can be associated with a residual current relay with separate coils, supplied without shunt trip

Front handle

- 3P
- 250 A

General characteristics

DPX™-IS 250 isolating switches - 63 to 250 A

- Isolating switches for on-load circuit breaking by visible isolation and positive action of the contacts
- Padlock integrated in the handle
- Connection with cage terminals
- Supplied with terminal shields
- Conform to IEC 60947-3
- Category of use AC 23 A
- Accept electrical auxiliaries
- Can be mounted on rail or on plate in XL³ enclosures

Documentation

Catalogue pages & additional information

- Description page (p.167)
- Technical page (p.170)
- DPXTM-IS 250 isolating switches

Installation instructions & related documents

- Y2376B

* All prices given are the manufacturer's list prices for professional customers, and are given for information only. They are not to be considered as a mandatory retail price - Basis : before-tax price list, May 2018

The information given in this e-catalogue (characteristics and dimensions) may be amended, and therefore does not represent an undertaking on our part. The e-catalogue is reserved for professionals only. You are also reminded that all products must be installed by a qualified professional in accordance with the installation rules.