Date: 24/04/2023

232.30.063 10 bar 2nd scale psi G1/4B lower back mount

Bourdon Tube Pressure Gauges, Safety Pattern

Item number:	48770556
Quantity:	1 pcs.
Order code:	232.30-C-BG410P-GB-3FHZCZZ-ZZZZZZZ 313D42ZF3W0 Z2Z-ICZZZZZ121ZZ LABEL-PG1DE-ZZZZZ
Overview:	232.30.063 10 bar 2nd scale psi G1/4B lower back mount Measuring System 316 SS Ingress protection: IP 54 class 1.6 front flange, polished SS Window: laminated safety glass Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C Pressure Gauge Standard: International (standard Europe) 2nd scale red stop-pin at zero *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Safety Pattern Series EN 837-1 Model: 232.30 Specifications according to data sheet: PM 02.04 Measuring system: stainless steel Case filling: without Nominal size: 063 mm Measuring range: gauge pressure range Scale range: 0...10 bar 2nd Scale or Special Scale: 2nd scale psi Process connection: G 1/4 B Connector location: lower back mount Mounting flange/bracket: front flange, polished SS Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.6 Overpressure safe: standard Case material: Stainless steel 1.4301 Case surface: bare Material pressure element: Measuring System 316 SS Case filling fluid: no filling, not to fill Ingress protection: IP 54

© 2023 - WIKA Instruments s.a.r.l.

Permissible medium temperature: + 200 °C
Permissible ambient temperature: -40 … +60 °C
Movement: stainless steel
Packaging: single packing
Pressure Gauge Standard: International (standard Europe)
color for 2.scale (inside): red RAL 3020
Manufacturer logo: *WIKA*
stop pin on dial: at zero
with Serial number
Permissible ambient temperature: -40 … +60 °C

© 2023 - WIKA Instruments s.a.r.l.