# Product data sheet
## Characteristics

# XZCB4L0100
## PvR cable - 4 x 0.5 mm2 - length 100 m



## Main

| | |
|---|---|
| Accessory / separate part type | Cable |

## Complementary

| | |
|---|---|
| Accessory / separate part designation | Bare cable |
| Accessory / separate part category | Cabling accessories |
| Cable length | 100 m |
| Material | PvR (PVC/NBR) sheath |
| Colour | Matt black |
| Cable cross section | 0.5 mm² |
| Total number of wires | 4 |
| Wire insulation material | PVC |
| Flame retardance | Class C2 conforming to NF C 32-070 |
| [Ue] rated operational voltage | 300 V |
| [Ui] rated insulation voltage | 2000 V conforming to NF C 32-201-1 |
| Bending radius | Minimum 3 x external diameter |
| Tensile strength | 10...35 N/mm² |
| Hardness | 70 shores A (tolerance: +/-5) |
| Product weight | 4.49 kg |

## Environment

| | |
|---|---|
| Ambient air temperature for operation | -35...90 °C |
| Ambient air temperature for storage | -40...100 °C |
| Environmental characteristic | Mineral resistant at 90 °C<br>Soluble resistant at 90 °C<br>Synthetic oils at 90 °C<br>Without silicone<br>Without unmoulding agent |

## Offer Sustainability

| | |
|---|---|
| RoHS (date code: YYWW) | Compliant - since 0601 - Schneider Electric declaration of conformity<br>Schneider Electric declaration of conformity |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |