Date: 11/04/2023

PSD-4; 0...1 bar abs ; one switching output (PNP/NPN) + 4...20 mA/0…10 V

PSD-4; 0...1 bar abs ; one switching output (PNP/NPN) + 4...20 mA/0…10 V

Item number:	48801274	
Quantity:	1 pcs.	
Order code:	PSD-4-EZ-BA310-GBSZ-WW-ZZ	W1011PS4Z-SZAB-P-GSFI
Overview:	PSD-4; 0...1 bar abs ; one switching output (PNP/NPN) + 4...20 mA/0…10 V Electronic pressure switch with display Output signal: one switching output (PNP/NPN) + 4...20 mA/0…10 V IO-Link: without Power supply: 15...35 V DC Measuring range: 0...1 bar abs Process connection: G 1/4 B Sealing: stainless steel Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86	
Details:	PSD-4; 0...1 bar abs ; one switching output (PNP/NPN) + 4...20 mA/0…10 V Electronic pressure switch with display Output signal: one switching output (PNP/NPN) + 4...20 mA/0…10 V IO-Link: without Power supply: 15...35 V DC Measuring range: 0...1 bar abs Process connection: G 1/4 B Sealing: stainless steel Media temperature: -20 … 85 °C (-4 ... +185 °F) El. connection: Circular connector M12x1 (4-pin) pin assignment el. connection: U+=1, U-=3, S+=2, SP1=4 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Specifications according to data sheet: PE 81.86	

© 2023 - WIKA Instruments s.a.r.l.