AREZZO™

A compact and lightweight goggle offering protection against liquid droplets as well as impacts.

The low-profile design enhances the field of vision and a comfortable fit is guaranteed thanks to the fully adjustable head strap.

SPECIAL FEATURES

- Ultra slim design
- Soft PVC comfort frame
- Fully adjustable pivotable head strap
- Weight: 56g



PANORAMIC VISION

PADDED SEAL

ULTRA-LIGHTWEIGHT

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR ◯	RLY00161	2C-1.2 1BTKN CE	EN 166 3BT CE	Impacts, Liquid Droplets	TECTON K&N Anti-scratch and Anti-fog

See overleaf for this product's technical specification ····►

AREZZO™

Riley

GENERAL SPECIFICATION

LENS BASE	6mm
WEIGHT	56g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	5
PER CARTON	100

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Durable and hard wearing
FRAME	Thermoplastic ElastomersTPE	Lightweight
HEAD BAND	Woven Elastic	Adjustable

LENS MARKINGS

LENS FILTER TYPE:
2C UV

SCALE NUMBER (SHADE):
1.2 Clear or Amber

Identity of the manufacturer

OPTICAL CLASS:
1 High optical quality

MECHANICAL STRENGTH:
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:
K Resistance to scratches by fine particles
N Resistance to fogging

CE Certification mark

FRAME MARKINGS

Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

FIELDS OF USE:
3 Liquid droplets or splashes

MECHANICAL STRENGTH:
B Medium energy impact, resists a 6mm, 0.86g ball at 120m/s
T Protection against high-speed particles at extreme temperatures

CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

www.riley-eyewear.com

E: info@riley-eyewear.com
T: +44 (0)161 877 4747
F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

Globus GROUP

EC-Type certification issued by:
0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom
The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment.
The manufacturer reserves the right to make any modifications it deems necessary.

© 2018 Globus (Shetland) Ltd | RILEY-DATA-AREZZO-0818