Specifications

Eaton 107207



Catalog Number: 107207

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Terminal plate, 3p, 1000mm², 1600A

General specifications

Product Name	**Catalog Number**
Eaton xEffect SASY 60i terminal plate	107207
EAN	**Product Length/Depth**
4015081069705	90 mm
Product Height	**Product Width**
204 mm	228 mm
Product Weight	**Compliances**
1.873 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

30 mm x 10 mm rail
Double T profile
60 mm system
Connection

Special features

Adapted to Eaton NZM4
Fixing direct over busbar terminals
Looping is possible

Type

60 mm system
Connection

Features

Self-extinguishing acc. UL 94

Width clamp

228 mm

Creepage resistance

CTI 200

Terminal contact area

5 mm x 28 mm

Busbar thickness - max

10 mm

Busbar thickness - min

5 mm

Busbar width - max

30 mm

Busbar width - min

12 mm

Conductor cross section - max

1000 mm²

Rated operational current (Ie) - max

1600 A

Functions

Connection kit
Connections

Resources

Brochures

eaton-xeffect-sasy60i-customer-success-story-css-wagner-mueller-en-us.pdf

Catalogs

Product Range Catalog Switching and protecting motors

eaton-xeffect-sasy-60i-fk4300-1167gb-en-us.pdf

Certification reports

eaton-xeffect-sasy-60i-declaration-of-conformity.pdf

Drawings

eaton-control-panels-xeffect-sasy-cover-dimensions-007.eps

eaton-control-panels-xeffect-sasy-clamp-terminal-dimensions.eps

eaton-control-panels-xeffect-sasy-terminal-3d-drawing.eps

Temperature resistance

Temperature resistant to 120 °C

Rated operation current (Ie)

1600 A

Suitable for

Flat rail

Three-pole

Round conductor connection

Sector conductor connection

Strip conductor connection

Material

Silicon free, chlorine free

Rated operational current

1600 A

Terminal capacity (conductor)

50 mm x 10 mm (2x)

10 segments of 50 mm x 1 mm (2x)

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia