Date: 05/04/2023

A2G-15 0 mbar...30 mbar

air2guide - Mechanical differential pressure gauge

Item number:	48784168	
Quantity:	1 pcs.	
Order code:	A2G-15-MAEN-ZZAA-SARF-SS1-ZZ-Z	2P
Overview:	A2G-15 0 mbar...30 mbar air2guide - Mechanical differential pressure gauge Second dial scale: without Set / drag pointer: externally adjustable red set pointer on window case fixing: wall mounting with 3 mounting screwed Output signal: 4...20 mA, 2-W Diaphragm: Standard silicon diaphragmPressure connection: 2x Angular, device side G1/8, for pipe diameter 4…6 mm (1/8"...1/4") Ingress protection: IP 54 Dial design: standard air2guide Segment design: standard air2guide serial number on dial: Serial number *...*Certificates: without	
Details:	air2guide - Mechanical differential pressure gauge with analog output signal A2G-15 Standard accessories 3 mounting screws Specifications according to data sheet: PV 17.40 Nominal size: 110 mm Accuracy class: class 3.0 (≤ 125 Pa Kl 5.0; ≤100 Pa Kl 10.0) Window: Macrolon (UV-stabilized) Kind of measurement: Differential pressure gauge with electrical output signal Unit: mbar Scale range: 0 mbar...30 mbar Set / drag pointer: externally adjustable red set pointer on window Output signal: 4 ... 20 mA, 2-wire case fixing: wall mounting with 3 mounting screwed Pressure connection: 2x Angular, device side G1/8, for pipe diameter 4…6 mm (1/8"...1/4") Diaphragm: Standard silicon diaphragm Ingress protection: IP 54 Dial design: standard air2guide Segment design: standard air2guide serial number on dial: Serial number *...* Certificates: without Second dial scale: without	

© 2023 - WIKA Instruments s.a.r.l.