PRODUCT-DETAILS

S800-CT2125

S800-CT2125 Cage Terminal



General Information

Extended Product Type	S800-CT2125
Product ID	2CCS800900R0181
EAN	7612271208264
Catalog Description	S800-CT2125 Cage Terminal
Long Description	The S800-CT2125 is a cage terminal kit. Inside of packaging are two termial to change 1-pole. The modification can be done very easy and fast.

Technical

Standards	IEC/EN 60947-2
Suitable For	S800S S800N S800C S800U S800PV-SP S800PV-SD S800PV-M-H
Tightening Torque	3.5 N·m
Recommended Screw Driver	Pozidriv 2

© 2024 ABB. All rights reserved.

Terminal Type	Screw Terminals

Material Compliance

RoHS Information	9AKK107680A3903
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20190320
REACH Declaration	9AKK108469A6125
REACH Information	No data - If REACH inform is not yet available for a certain product
REACH Date	20190320
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
Degree of Protection	acc. to IEC 60529 IP20
Environmental Information	2CCY413207D0203

Dimensions

Product Net Width	27 mm
Product Net Height	12 mm
Product Net Depth / Length	20 mm
Product Net Weight	34 g

Ordering

Package Level 1 Units	bag 2 piece
Package Level 1 Gross Weight	70 g

Certificates and Declarations

Declaration of Conformity - CE	No declaration needed

Installation

Instructions and Manuals	9AKK106930A3418

Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208

© 2024 ABB. All rights reserved.

Classifications

ETIM 8	EC002278 - Distributor assembly miniature circuit breaker (MCB)
ETIM 9	EC002278 - Distributor assembly miniature circuit breaker (MCB)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85389040
eClass	V11.0 : 27400617
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs Accessories



© 2024 ABB. All rights reserved.