Date: 22/01/2024

232.50.100 40 bar G1/2B lower back mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number:	9010580
Quantity:	1 pcs.
Order code:	232.50-E-BG440Z-GD-3ZHZCZZ-ZZZZZZZ 213D31ZI3W0 Z2Z-IZZZZZZ12ZZZ LABEL-PG1DE-ZZZZZ
Overview:	232.50.100 40 bar G1/2B lower back mount Measuring System 316L Ingress protection: IP 65 class 1.0 Window: laminated safety glass Permissible ambient temperature: -40 … +60 °C Permissible medium temperature: + 200 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Stainless Steel Series Model: 232.50 Specifications according to data sheet: PM 02.02 Measuring system: stainless steel Case filling: without Nominal size: 100 mm Scale range: 0...40 bar Process connection: G 1/2 B Connector location: lower back mount Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.0 Overpressure safe: standard Case material: Stainless steel 1.4301 Case surface: bare Material pressure element: Measuring System 316L Case filling fluid: prepared for filling Ingress protection: IP 65 Permissible medium temperature: + 200 °C Permissible ambient temperature: -40 … +60 °C Movement: stainless steel Packaging: single packing Pressure Gauge Standard: International (standard Europe) Manufacturer logo: *WIKA*

© 2024 - WIKA Instruments s.a.r.l.

Date: 22/01/2024

with Serial number

© 2024 - WIKA Instruments s.a.r.l.