
TIMKEN

The Timken Company
4500 Mt Pleasant St. NW
N. Canton, OH 44720
Phone: (234) 262-3000
E-Mail: CustomerCAD@timken.com • **Web site:** www.timken.com

Timken Part Number HM89440 - HM89410, Tapered Roller Bearings - TS (Tapered Single) Imperial

This is the most basic and most widely used type of tapered roller bearing. It consists of two main separable parts: the cone (inner ring) assembly and the cup (outer ring). It is typically mounted in opposing pairs on a shaft.





Specifications | Dimensions | Abutment and Fillet Dimensions | Basic Load Ratings | Factors

Specifications

Series	HM89400
Cone Part Number	HM89440
Cup Part Number	HM89410
Design Units	Imperial
Bearing Weight	0.700 Kg 1.50 lb
Cage Type	Stamped Steel

Dimensions

d - Bore	31.750 mm 1.2500 in
D - Cup Outer Diameter	76.2 mm 3 in

B - Cone Width	28.575 mm 1.1250 in
C - Cup Width	23.020 mm 0.9063 in
T - Bearing Width	29.370 mm 1.1563 in

Abutment and Fillet Dimensions

R - Cone Backface "To Clear" Radius[1]	0.760 mm 0.03 in
r - Cup Backface "To Clear" Radius[2]	3.30 mm 0.130 in
da - Cone Frontface Backing Diameter	44.45 mm 1.75 in
db - Cone Backface Backing Diameter	45.47 mm 1.79 in
Da - Cup Frontface Backing Diameter	73.90 mm 2.91 in
Db - Cup Backface Backing Diameter	61.98 mm 2.44 in
Ab - Cage-Cone Frontface Clearance	2 mm 0.08 in
Aa - Cage-Cone Backface Clearance	1.5 mm 0.06 in
a - Effective Center Location[3]	-5.60 mm -0.22 in


Basic Load Ratings

C90 - Dynamic Radial Rating (90 million revolutions)[4]	28600 N 6440 lbf
C1 - Dynamic Radial Rating (1 million revolutions)[5]	110000 N 24800 lbf
C0 - Static Radial Rating	119000 N 26700 lbf
C_{a90} - Dynamic Thrust Rating (90 million revolutions)[6]	26800 N 6020 lbf

Factors

K - Factor[7]	1.07
e - ISO Factor[8]	0.55
Y - ISO Factor[9]	1.1
G1 - Heat Generation Factor (Roller-Raceway)	28.9
G2 - Heat Generation Factor (Rib-Roller End)	13.1
Cg - Geometry Factor	0.0883

[1] These maximum fillet radii will be cleared by the bearing corners.
[2] These maximum fillet radii will be cleared by the bearing corners.
[3] Negative value indicates effective center inside cone backface.
[4] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values.
[5] Based on 1 x 10^6 revolutions L_{10} life, for the ISO life calculation method.
[6] Based on 90 x 10^6 revolutions L_{10} life, for The Timken Company life calculation method. C_{90} and C_{a90} are radial and thrust values for a single-row, $C_{90(2)}$ is the two-row radial value.
[7] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[8] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.
[9] These factors apply for both inch and metric calculations. Consult your Timken representative for instruction on use.



IMPERIAL UNITS

ISO Factor - e	0.55	
ISO Factor - Y	1.1	
Bearing Weight	1.5	lb
Number of Rollers Per Row	18	
Effective Center Location	-0.22	inch

TIMKEN®

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

HM89440 - HM89410
TS BEARING ASSEMBLY

K Factor	1.07	
Dynamic Radial Rating - C90	28600	lbf
Dynamic Thrust Rating - Ca90	26800	lbf
Static Radial Rating - C0	119000	lbf
Dynamic Radial Rating - C1	110000	lbf

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY