Specifications

Eaton 266748



Catalog Number: 266748

Eaton Moeller series NZM - Molded Case Circuit Breaker. Protection against contact with a finger, IP2X, 3p, size 1, A

General specifications

Product Name
Eaton Moeller series NZM connection type

Catalog Number
266748

EAN
4015082667481

Product Length/Depth
50 mm

Product Height
30 mm

Product Width
60 mm

Product Weight
0.029 kg

Compliances
IEC
UL/CSA
RoHS conform

Powering Business Worldwide

Product specifications

Used with

NZM1, PN1, NS1

Cover NZM1-XKSA or NZM1 or NZM1...(C)NA und N(S)1...NA

Type

Accessory

Terminal

IP2X protection against

contact with finger

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf

eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Compact circuit-breakers and switch-disconnectors up to 1600 A

Declarations of conformity

DA-DC-03_NZM1

Drawings

eaton-circuit-breaker-terminals-nzm-mccb-dimensions.eps

eaton-circuit-breaker-contact-nzm-mccb-3d-drawing-002.eps

Installation instructions

eaton-circuit-breaker-finger-proof-ip2x-nzm1-2-3-il01219008z.pdf

Installation videos

Introduction of the new digital circuit breaker NZM

The new digital NZM Range

mCAD model

nzm1_xipa

nzm1_xipa.stp

Technical data sheets

eaton-nzm-technical-information-sheet

Warranty guides

Selling Policy 25-000 - Distribution and Control Products and Services

evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM1

Degree of protection

IP2X (protection against contact with a finger)

Number of poles

Three-pole

Phase separator type

Other



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia