NTT04

24 Hour/7 Day Compact Electronic General Purpose Timeswitch with Voltage Free Contacts



Features & Benefits

- 4 ON/4 OFF Programme Periods Per Day, Up To 28 ON/28 OFF Programmes Per Week
- Shortest Switching Time 1 Min
- Extra Large ‘Easy View’ Screen with Blue LED Backlighting
- Red LED ‘Mains ON’ and Green LED ‘Output’
- Large Easy Push Programme Buttons
- Self-Cancelling Override Button To Next Programme Change
- Optional 1 & 2 Hour Boost Button Automatic Summer/Winter Time Change
- Rechargeable Battery Back-up
- Fits a Standard Flush Or Surface Mount Box Min 32mm
- Volt Free Contacts

Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Surface Mount
Earth Class Rating	Class II
Operating Temperature	0°C to 40°C

Data sheet
NTT04

Time / Immersion & General Purpose Timeswitches

Ingress Protection Rating	IP20
Setting Type	Digital
Battery Type	NiMH 1.2V 80mAh Rechargeable Battery
Back Box Minimum Depth (mm)	32
Program Modes	24 Hour/7 Day, 1 Hour/2Hour Boost
Switch type	Single Pole
Voltage Free Contacts	Normally Open, Normally Closed (Changeover)
Mounting Hole Centres (mm)	60
Standby Consumption	<0.96W
Number of Channels	1
Switch rating	16A Resistive , 2400W Halogen, 750W Fluorescent, 100W CFL, 100W LED
Shortest Switching Time	1 Minute
Programmable Slots	4 ON 4 OFF
Permanent ON Facility	Yes (Override ON)
Cable Capacity (mm2)	1.5 - 2.5mm2 Flexible Cable
Cable Entry(s)	Back Entry

General

Weight (g)	168
Height (mm)	92
Width (mm)	92
Depth (mm)	59
Body Construction	Polycarbonate
Product Colour	White

Subject to technical changes and misprints

Data sheet
NTT04

Time / Immersion & General Purpose Timeswitches

Accessories (Included)	Fittings (Rawl Plugs, Screws)
EAN Number	5012483012321
Guarantee Period	3 Years

Line Diagrams

