Date: 11/04/2023

A5500/4, NS100, 0...120°C, L1=143x6mm

Bimetal thermometer, stainless steel version

Item number:	48750699
Quantity:	1 pcs.
Order code:	A5500 -4-C1F-ND-B143GZZ-AHAZZZZ TB FZZZEPZSVID-AZ1ZZZZZ1ZZZZ
Overview:	A5500/4, NS100, 0...120°C, L1=143x6mm Process connection: 1/2 NPT, axial flat instrument glass, class 1 per EN 13190 Explosion protection: ATEX Ex h Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) *WIKA* Serial number *...*
Details:	Bimetal thermometer, stainless steel version Specifications according to data sheet: TM 55.01 Case: stainless steel Stem material: stainless steel Model: A 5500, nominal size 100, location of stem centre back (axial) Connection design: 4, compression fitting, sliding on stem Unit: °C Scale range: 0 °C ... 120 °C Process connection: 1/2 NPT Stem diameter: 6 mm Insertion length L1: 143 mm Window: flat instrument glass Zone: Gas Zone 1 / Dust Zone 21 (II 2G Ex h IIC T6 ... T1 Gb X / II 2D Ex h IIIC T85 °C … T450 °C Db X) Case: Stainless steel Connector location: axial Version: standard Stem material: stainless steel Permissible ambient temperature: -40 ... +70 °C Manufacturer logo: *WIKA* Accuracy class: class 1 per EN 13190 Ingress protection: IP 65 serial number on dial: Serial number *...* Explosion protection: ATEX Ignition protection type: Ex h

© 2023 - WIKA Instruments s.a.r.l.