Date: 24/01/2024

233.50.160 -1/+5 bar G1/2B lower mount

Bourdon Tube Pressure Gauges, Stainless Steel

Item number:	8566496
Quantity:	1 pcs.
Order code:	233.50-F-BV360Z-GD-UZHZCZZ-ZZZZZZZ 213D3AZIYG0 Z2Z-IZZZZZZ12ZZZ LABEL-PG1DE-ZZZZZ
Overview:	233.50.160 -1/+5 bar G1/2B lower mount Measuring System 316L Ingress protection: IP 65 class 1.0 Window: laminated safety glass Case filling fluid: glycerine Permissible ambient temperature: -20 … +60 °C Permissible medium temperature: + 100 °C Pressure Gauge Standard: International (standard Europe) *WIKA* with Serial number Label: WIKA standard without / with Tag-number
Details:	Bourdon Tube Pressure Gauges, Stainless Steel Series Model: 233.50 Specifications according to data sheet: PM 02.02 Measuring system: stainless steel Case filling: with Nominal size: 160 mm Scale range: -1...+5 bar Process connection: G 1/2 B Connector location: lower mount Window: laminated safety glass Pointer: standard pointer Accuracy class: class 1.0 Overpressure safe: standard Case material: Stainless steel 1.4301 Case surface: bare Material pressure element: Measuring System 316L Case filling fluid: glycerine Ingress protection: IP 65 Permissible medium temperature: + 100 °C Permissible ambient temperature: -20 … +60 °C Movement: stainless steel Packaging: single packing Pressure Gauge Standard: International (standard Europe)

© 2024 - WIKA Instruments s.a.r.l.

Date: 24/01/2024

Manufacturer logo: *WIKA*
with Serial number

© 2024 - WIKA Instruments s.a.r.l.