PERFORMANCE MADE SMARTER



Temperature / mA converter

9113B

– Input for RTD, TC and mA
– Active / passive mA output via the same two terminals
– 1 or 2 channels
– Can be supplied separately or installed on power rail, PR type 9400
– SIL 2-certified via Full Assessment


Advanced features
- Configuration and monitoring by way of detachable display front (PR 4511/4501); process calibration and signal simulation.
- Copying of the configuration from one device to others of the same type via the display front.
- TC inputs can use either the internal CJC or a terminal with a built-in Pt100 sensor (PR 5910Ex, channel 1 / PR 5913Ex, channel 2) for higher accuracy.
- Advanced monitoring of internal communication and stored data.
- SIL 2 functionality is optional and must be activated in a menu point.

Application
- The device can be mounted in the safe area and in zone 2 / cl. 1 div. 2 and receive signals from zone 0, 1, 2 and zone 20, 21, 22 including M1 / Class I/II/III, Div. 1, Gr. A-G.
- Conversion and scaling of temperature (Pt, Ni and TC) and active current signals.
- The 9113 has been designed, developed and certified for use in SIL 2 applications according to the requirements of IEC 61508.

Technical characteristics
- 1 green and 2 red front LEDs indicate operation status and malfunction.
- 2.6 kVAC galvanic isolation between input, output and supply.

Mounting
- The devices can be mounted vertically or horizontally without distance between neighbouring units.

Applications



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type	Unit channels	
9113B	Single	: A
	Double	: B

Environmental Conditions

Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +85°C
Calibration temperature	20...28°C
Relative humidity	< 95% RH (non-cond.)
Protection degree	IP20
Installation in	Pollution degree 2 & measurement / overvoltage cat. II

Mechanical specifications

Dimensions (HxWxD)	109 x 23.5 x 104 mm
Dimensions (HxWxD) w/ 4501 / 4511	109 x 23.5 x 116 / 131 mm
Weight approx.	250 g
Weight incl. 4501 / 4511 (approx.)	265 g / 350 g
DIN rail type	DIN EN 60715/35 mm
Wire size	0.13...2.08 mm^2 AWG 26...14 stranded wire
Screw terminal torque	0.5 Nm
Vibration	IEC 60068-2-6
2...13.2 Hz	±1 mm
13.2...100 Hz	±0.7 g

Common specifications

Supply

Supply voltage	19.2...31.2 VDC
Fuse	400 mA SB / 250 VAC
Max. required power	≤ 0.8 W / ≤ 1.4 W (1 ch. / 2 ch.)
Max. power dissipation, 1 / 2 ch	≤ 0.8 W / ≤ 1.4 W

Isolation voltage

Test /working: Input to any	2.6 kVAC / 300 VAC reinforced isolation
Analog output to supply	2.6 kVAC / 300 VAC reinforced isolation
Status relay to supply	1.5 kVAC / 150 VAC reinforced isolation

Response time

Temperature input, programmable (0...90%, 100...10%)	1...60 s
mA / V input (programmable)	0.4...60 s
Programming	Communication enabler 4511 / Programming front 4501
Signal / noise ratio	Min. 60 dB (0...100 kHz)
Signal dynamics, input	24 bit
Signal dynamics, output	16 bit
Accuracy	Better than 0.1% of selected range
EMC immunity influence	< ±0.5% of span
Extended EMC immunity: NAMUR NE21, A criterion, burst	< ±1% of span

Input specifications

RTD input

RTD type	Pt10/20/50/100/200/250/300/Pt400/500/1000; Ni50/100/120/1000
Cable resistance per wire (max.)	50 Ω
Sensor current	Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire)	< 0.002 Ω / Ω
Sensor error detection	Programmable ON / OFF

TC input

Thermocouple type	B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC) via ext. sensor in connector 5910	20...28°C ≤ ±1°C, -20...20°C / 28...70°C ≤ 2°C
CJC via internally mounted sensor	±(2.0°C + 0.4°C * Δt)
Δt =	Internal temp.-ambient temp.
Sensor error detection	Programmable ON or OFF (only wire breakage)
Sensor error current: When detecting / else	Nom. 2 µA / 0 µA

Current input

Measurement range	0...23 mA
Programmable measurement ranges	0...20 and 4...20 mA
Input resistance	Nom. 20 Ω + PTC 50 Ω
Sensor error detection	Programmable ON / OFF

Output specifications

Current output

Signal range	0...23 mA
Programmable signal ranges	0...20/4...20/20...0/20...4 mA
Load (@ current output)	≤ 600 Ω
Load stability	≤ 0.01% of span / 100 Ω
Sensor error indication	0 / 3.5 / 23 mA / none
NAMUR NE43 Upscale/Downscale	23 mA / 3.5 mA
Output limitation, on 4...20 and 20...4 mA signals	3.8...20.5 mA
Output limitation, on 0...20 and 20...0 mA signals	0...20.5 mA
Current limit	≤ 28 mA

Passive 2-wire mA output

Max. external 2-wire supply	26 VDC
Max. load resistance [Ω]	(Vsupply-3.5)/0.023 A
Effect of external 2-wire supply voltage variation	< 0.005% of span / V

Status relay

Max. voltage	110 VDC / 125 VAC
Max. current	0.3 ADC / 0.5 AAC
Max. AC power	62.5 VA / 32 W

Observed authority requirements

EMC	2014/30/EU
LVD	2014/35/EU
RoHS	2011/65/EU
EAC	TR-CU 020/2011

Approvals

ATEX 2014/34/EU	KEMA 07ATEX0148 X
IECEx	KEM 09.0052X
FM	3038279-C
INMETRO	DEKRA 16.0003 X
UL	UL 61010-1
EAC Ex TR-CU 012/2011	RU C-DK.GB08.V.00410
DNV-GL Marine	Stand. f. Certific. No. 2.4
CCOE	P337349/3
SIL	SIL 2 certified & fully assessed acc. to IEC 61508