Specifications

Eaton 171340



Catalog Number: 171340

Eaton Moeller® series SL4 Flashing light module, white, LED, 24 V

General specifications

Product Name	Catalog Number
Eaton Moeller® series SL4 Flashing light module	171340
	EAN
	4015081678761
Product Length/Depth	**Product Height**
43 mm	75 mm
Product Width	**Product Weight**
43 mm	0.042 kg

Certifications

UL 508
UL report applies to both US and Canada
UL
UL Category Control No.: NKCR
UL File No.: E29184
Certified by UL for use in Canada
IEC/EN 60947-5-1
CSA-C22.2 No. 94-91
CSA Class No.: NKCR7
IEC/EN 60529
CE
CSA-C22.2 No. 14-10

Powering Business Worldwide

Features & Functions

Color
Other

Enclosure color
Black

Functions
Blinker light

Light modules
LED

Number of modules
Max. 10 (with base for mounting on both sides)
Max. 5 (with standard base)

General

Connection to SmartWire-DT
No

Current consumption
50 mA at 24 V AC/DC

Degree of protection
IP66
NEMA 4X

Flashing frequency
2 Hz

Lifespan, electrical
100,000 h

Light type
Flashing light

Material
Cap: Polycarbonate (PC)
Enclosure: Polycarbonate (PC)

Mounting position
As required

Overvoltage category
III

Pollution degree
3

Product Category
SL signal towers

Radiation angle
360 °

Rated impulse withstand voltage (Uimp)
4000 V AC

Shock resistance
15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Mechanical, According to IEC/EN 60068-2-27

Type
Flashing light module

Voltage type
AC/DC

Climatic environmental conditions

Ambient operating temperature - min

-30 °C

Ambient operating temperature - max

60 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Electrical rating

Leakage current

0.003 A

Rated insulation voltage (Ui)

250 V

Rated operational voltage (Ue) at AC - min

24 V

Rated operational voltage (Ue) at AC - max

24 V

Rated operational voltage (Ue) at DC - min

24 V

Rated operational voltage (Ue) at DC - max

24 V

Resources

Brochures

SL4, SL7, SLC Stack light overview brochure BR047017

Catalogs

eaton-rmq-titan-brochure-br047004en-en-us.pdf

eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf

Declarations of conformity

DA-DC-00004257.pdf

DA-DC-00004253.pdf

Drawings

eaton-operating-sl4-continuous-light-dimensions.eps

eaton-operating-sl7-flashing-light-symbol.eps

eaton-operating-button-sl7-continuous-light-symbol-003.eps

eCAD model

ETN.171340.edz

Installation instructions

IL047001ZU

Installation videos

Signal towers SL4 and SL7

mCAD model

DA-CD-sl4_bfl4

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia