Date: 11/04/2023

ERL3/8"-LOOS-L3,610/14-V52A-2PVC

ERL3/8"-LOOS-L3,610/14-V52A-2PVC

Item number: 48809966

Quantity: 1 pcs.

Order code: FLS-CBMZZ000501000BZM02HAZZ0310O0430O3565SZZZZZZZ
FLRVIA36103NZZZZ

Overview:
ERL3/8"-LOOS-L3,610/14-V52A-2PVC
Float Switch Type FLS-SE
Material: Stainless steel 316L (EN 1.4404)
Pressure: 0.5 bar
Temperature range: -20°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Cable PVC 2 m
Process connection: Mounting thread upwards 3/8"BSP
Switch function 1: Opening on rising level (SPST) 310 mm
Switch function 2: Opening on rising level (SPST) 430 mm
Switch function 3: Closing on rising level (SPST) 3565 mm
Switch rating: max. AC 50V; 100VA; 1A / DC 75V; 50W; 0.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 3 pcs
Guide tube: OD 14 mm Insertion length (L): 3610 mm
Float stop: Float collar
Float can't be mounted through the connection nozzle
Weight: 2.5 kg
Brand name: Kubler France

Details:
ERL3/8"-LOOS-L3,610/14-V52A-2PVC
Float Switch Type FLS-SE
Material: Stainless steel 316L (EN 1.4404)
Pressure: 0.5 bar
Temperature range: -20°C up to 80°C
Fluid density: 1000 kg/m³
Electrical connection: Cable PVC 2 m
Process connection: Mounting thread upwards 3/8"BSP
Switch function 1: Opening on rising level (SPST) 310 mm
Switch function 2: Opening on rising level (SPST) 430 mm
Switch function 3: Closing on rising level (SPST) 3565 mm
Switch rating: max. AC 50V; 100VA; 1A / DC 75V; 50W; 0.5A
Float: Stainless steel 316Ti V52A; Float outer diameter: 52 mm
Number of floats: 3 pcs
Guide tube: OD 14 mm Insertion length (L): 3610 mm
Float stop: Float collar
Float can't be mounted through the connection nozzle
Weight: 2.5 kg

© 2023 - WIKA Instruments s.a.r.l.

Date: 11/04/2023

Brand name: Kubler France

© 2023 - WIKA Instruments s.a.r.l.