DATASHEET



ZS 336-11Z-M20

- Snap action with constant contact pressure up to switching point
- 1 Cable entry M 20 x 1.5
- Design to EN 50041
- Thermoplastic enclosure
- Double-insulated
- Good resistance to oil and petroleum spirit
- Wide range of alternative actuators
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

Product type description	ZS 336-11Z-M20
Article number (order number)	131156136
EAN (European Article Number)	8905236103674
eCl@ss number, version 12.0	27-27-26-01
eCl@ss number, version 11.0	27-27-26-01
eCl@ss number, version 9.0	27-27-26-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

General data

Housing construction form	Norm construction design
Actuator type to EN 50041	B
Housing material	Plastic, glass-fibre-reinforced
Gross weight	105 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety classification

Standards	BG-GS-ET-15 EN ISO 13849-1 EN IEC 60947-5-1
Mission time	20 Year(s)

Safety classification - Safety outputs

B_{10D} Normally-closed contact (NC)	20,000,000 Operations

Mechanical data

Actuating element	Plunger
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	12 N
Actuating speed, maximum	0.5 m/s
Note Bounce duration	Bounce duration in accordance with actuating speed

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm²
Cable section, maximum	2.5 mm²
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	38 mm

Width of sensor	40.5 mm
Height of sensor	103.5 mm

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature	-30 ... +80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	NO contact, NC contact
Switching principle	Snap action
Maximum switching frequency	5,000 /h
Switchover time, maximum	2 ms
Material of the contacts, electrical	Silver

Ordering code

Product type description:
(1)(2) 336-(3)(4)-(5)-(6)-(7)-(8)-(9)

(1)

Z	Snap action

T	Slow action (not for AF/S)

(2)

S	Plunger S
R	Roller plunger R
H	Roller lever H
10H	Rod lever 10H
7H	Roller lever 7H
1K	Offset roller lever 1K
3K	Angle roller lever 3K
RMS	Brass roller

(3)

11	1 NO contact/1 NC contact
02	2 NC contact
20	2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)
01/01	1 NC contact left / 1 NC contact right

(4)

Y	IP 65
Z	IP 67

(5)

	without latching
R	with latching

(6)

H	Slow action with staggered contacts
UE	Slow action with overlapping contacts

(7)

without	Cable entry M20
NPT	Cable entry NPT 1/2"
ST	M12 connector with A-coding

ST-2310	M12 connector with B-coding

(8)

2138	Roller lever 7H for position switches with safety function

(9)

1637	Gold-plated contacts


Pictures

Product picture (catalogue individual photo)




ID: k336sf01
| 632.4 kB | .jpg | 352.778 x 701.322 mm - 1000 x 1988 px - 72 dpi
| 78.9 kB | .png | 74.083 x 147.108 mm - 210 x 417 px - 72 dpi
| 30.5 kB | .jpg | 62.089 x 123.472 mm - 176 x 350 px - 72 dpi

Dimensional drawing basic component




ID: 1-336g01
| 51.4 kB | .cdr |
| 4.1 kB | .png | 74.083 x 51.506 mm - 210 x 146 px - 72 dpi
| 107.0 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 px - 72 dpi

Dimensional drawing actuator




ID: 1s336g01
| 48.9 kB | .cdr |
| 2.7 kB | .png | 74.083 x 52.211 mm - 210 x 148 px - 72 dpi
| 52.6 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703 px - 72 dpi

Switch travel diagram



ID: kr335s12
| 25.9 kB | .cdr |
| 2.4 kB | .png | 74.083 x 39.511 mm - 210 x 112 px - 72 dpi
| 67.0 kB | .jpg | 352.778 x 188.031 mm - 1000 x 533 px - 72 dpi

Diagram



ID: k1o1sk01
| 52.2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407 px - 72 dpi
| 2.6 kB | .png | 74.083 x 29.986 mm - 210 x 85 px - 72 dpi

Schmersal India Pvt. Ltd., Plot No - G-7/1, Ranjangaon MIDC, Tal. - Shirur, Dist.- Pune 412 220
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 26/12/2024, 10:34 am