# DATASHEET - DA1-127D0FB-B66C

**Variable frequency drive, 230 V AC, 1-phase, 7 A, 1.5 kW, IP66/NEMA 4X, Radio interference suppression filter, OLED display**

| | |
|---|---|
| **Part no.** | **DA1-127D0FB-B66C** |
| | **169349** |
| **EL Number (Norway)** | **4137817** |

## General specifications

| | |
|---|---|
| Product name | Eaton DA1 Variable frequency drive |
| Part no. | DA1-127D0FB-B66C |
| EAN | 4015081657988 |
| Product Length/Depth | 239.3 millimetre |
| Product height | 257 millimetre |
| Product width | 188 millimetre |
| Product weight | 4.8 kilogram |
| Certifications | RCM<br>UL Category Control No.: NMMS, NMMS7<br>IEC/EN 61800-3<br>CE<br>RoHS, ISO 9001<br>UkrSEPRO<br>UL report applies to both US and Canada<br>Safety: EN 61800-5-1: 2003<br>IEC/EN61800-3<br>Specification for general requirements: IEC/EN 61800-2<br>EAC<br>UL File No.: E172143<br>Certified by UL for use in Canada<br>IEC/EN61800-5<br>CSA-C22.2 No. 14<br>CUL<br>UL<br>UL 508C |
| Product Tradename | DA1 |
| Product Type | Variable frequency drive |
| Product Sub Type | None |
| Catalog Notes | The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. |

## General information

| | |
|---|---|
| Cable length | C2 ≤ 5 m, Radio interference level, maximum motor cable length<br>200 m, screened, with motor choke, maximum permissible, Motor feeder<br>300 m, unscreened, with motor choke, maximum permissible, Motor feeder<br>100 m, screened, maximum permissible, Motor feeder<br>C3 ≤ 25 m, Radio interference level, maximum motor cable length<br>C1 ≤ 1 m, Radio interference level, maximum motor cable length<br>150 m, unscreened, maximum permissible, Motor feeder |
| Communication interface | Ethernet IP, optional<br>DeviceNet, optional<br>OP-Bus (RS485), built in<br>PROFIBUS, optional<br>CANopen®, built in<br>EtherCAT, optional<br>PROFINET, optional<br>Modbus-TCP, optional<br>Modbus RTU, built in |
| Connection to SmartWire-DT | No |
| Degree of protection | IP66<br>NEMA 4X |
| Electromagnetic compatibility | 1st and 2nd environments (according to EN 61800-3) |
| Fitted with: | IGBT inverter<br>Additional PCB protection<br>Internal DC link<br>PC connection<br>Brake chopper<br>Breaking resistance<br>Radio interference suppression filter<br>OLED display<br>Control unit |
| Frame size | FS2 |
| Functions | 4-quadrant operation possible |

| | |
|---|---|
| Mounting position | Vertical |
| Product Category | Variable frequency drives |
| Protection | Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4) |
| Protocol | TCP/IP<br>DeviceNet<br>Other bus systems<br>PROFINET IO<br>CAN<br>EtherNet/IP<br>MODBUS<br>PROFIBUS |
| Safety function/level | STO (Safe Torque Off, SIL2, PLc Cat 2) |
| Suitable for | Branch circuits, (UL/CSA) |
| Radio interference class | C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.<br>C1: for conducted emissions only |

## Climatic environmental conditions

| | |
|---|---|
| Ambient operating temperature - min | -10 °C |
| Altitude | Above 1000 m with 1 % derating per 100 m<br>Max. 1000 m<br>Max. 4000 m |
| Ambient operating temperature - max | 40 °C |
| Ambient operating temperature at 150% overload - min | -10 °C |
| Ambient operating temperature at 150% overload - max | 40 °C |
| Ambient storage temperature - min | -40 °C |
| Ambient storage temperature - max | 60 °C |
| Climatic proofing | < 95 average relative humidity (RH), no condensation, no corrosion |

## Main circuit

| | |
|---|---|
| Efficiency | 95.8 % (η) |
| Heat dissipation at current/speed | 77 W at 100% current and 90% speed<br>66 W at 100% current and 50% speed<br>55 W at 100% current and 0% speed<br>54 W at 50% current and 90% speed<br>46 W at 50% current and 50% speed<br>39 W at 50% current and 0% speed<br>38 W at 25% current and 50% speed<br>30 W at 25% current and 0% speed |
| Input current ILN at 150% overload | 12.9 A |
| Leakage current at ground IPE - max | 2.49 mA |
| Mains switch-on frequency | Maximum of one time every 30 seconds |
| Mains voltage - min | 200 V |
| Mains voltage - max | 240 V |
| Operating mode | Speed control with slip compensation<br>Sensorless vector control (SLV)<br>U/f control<br>Optional: Vector control with feedback (CLV) |
| Output frequency - min | 0 Hz |
| Output frequency - max | 500 Hz |
| Output voltage (U2) | 230 V AC, 3-phase<br>240 V AC, 3-phase |
| Overload current IL at 150% overload | 10.5 A |
| Rated control supply voltage | 10 V DC (Us, max. 10 mA) |
| Rated frequency - min | 48 Hz |
| Rated frequency - max | 62 Hz |
| Rated operational current (Ie) at 150% overload | 7 A |
| Rated operational power at 220/230 V, 50 Hz, 1-phase | 1.5 kW |
| Rated operational voltage | 230 V AC, 1-phase<br>240 V AC, 1-phase |
| Resolution | 0.1 Hz (Frequency resolution, setpoint value) |
| Short-circuit protection rating | 20 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring |
| Starting current - max | 200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section |
| Supply frequency | 50/60 Hz |
| Switching frequency | 16 kHz, 4 - 32 kHz adjustable (audible), fPWM, Power section, Main circuit |

| | |
|---|---|
| System configuration type | AC supply systems with earthed center point |
| Voltage rating - max | 240 V AC |

## Motor rating

| | |
|---|---|
| Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload | 6.8 A |
| Assigned motor current IM at 230 V, 50 Hz, 150% overload | 6.3 A |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | 2 HP |

## Apparent power

| | |
|---|---|
| Apparent power at 230 V | 2.79 kV·A |
| Apparent power at 240 V | 2.91 kV·A |

## Braking function

| | |
|---|---|
| Braking resistance | 50 Ω |
| Braking torque | Max. 100 % of rated operational current Ie with external braking resistor - Main circuit<br>Max. 100 % of rated operational current Ie, variable, DC - Main circuit<br>Max. 30 % MN, Standard - Main circuit |
| Switch-on threshold for the braking transistor | 390 V DC |

## Control circuit

| | |
|---|---|
| Number of inputs (analog) | 2 |
| Number of inputs (digital) | 5 |
| Number of outputs (analog) | 2 |
| Number of outputs (digital) | 2 |
| Number of relay outputs | 2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1)) |
| Rated control voltage (Uc) | 24 V DC (external, max. 100 mA) |

## Design verification

| | |
|---|---|
| Equipment heat dissipation, current-dependent Pvid | 63 W |
| Heat dissipation capacity Pdiss | 0 W |
| Heat dissipation per pole, current-dependent Pvid | 0 W |
| Rated operational current for specified heat dissipation (In) | 7 A |
| Static heat dissipation, non-current-dependent Pvs | 0 W |
| 10.2.2 Corrosion resistance | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | Meets the product standard's requirements. |
| 10.2.5 Lifting | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

# Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)

| Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency / Servo converter = < 1 kV (ecl@ss13-27-02-31-01 [AKE177019]) | | |
|---|---|---|
| Mains voltage | V | 200 - 240 |
| Mains frequency | | 50/60 Hz |
| Number of phases input | | 1 |
| Number of phases output | | 3 |
| Max. output frequency | Hz | 500 |
| Max. output voltage | V | 250 |
| Nominal output current I2N | A | 7 |
| Max. output at quadratic load at rated output voltage | kW | 1.5 |
| Max. output at linear load at rated output voltage | kW | 1.5 |
| Power consumption | W | 63 |
| Relative symmetric net frequency tolerance | % | 10 |
| Relative symmetric net voltage tolerance | % | 10 |
| Number of analogue outputs | | 2 |
| Number of analogue inputs | | 2 |
| Number of digital outputs | | 2 |
| Number of digital inputs | | 5 |
| With control element | | Yes |
| Application in industrial area permitted | | Yes |
| Application in domestic- and commercial area permitted | | Yes |
| Supporting protocol for TCP/IP | | Yes |
| Supporting protocol for PROFIBUS | | Yes |
| Supporting protocol for CAN | | Yes |
| Supporting protocol for INTERBUS | | No |
| Supporting protocol for ASI | | No |
| Supporting protocol for KNX | | No |
| Supporting protocol for Modbus | | Yes |
| Supporting protocol for Data-Highway | | No |
| Supporting protocol for DeviceNet | | Yes |
| Supporting protocol for SUCONET | | No |
| Supporting protocol for LON | | No |
| Supporting protocol for PROFINET IO | | Yes |
| Supporting protocol for PROFINET CBA | | No |
| Supporting protocol for SERCOS | | No |
| Supporting protocol for Foundation Fieldbus | | No |
| Supporting protocol for EtherNet/IP | | Yes |
| Supporting protocol for AS-Interface Safety at Work | | No |
| Supporting protocol for DeviceNet Safety | | No |
| Supporting protocol for INTERBUS-Safety | | No |
| Supporting protocol for PROFIsafe | | No |
| Supporting protocol for SafetyBUS p | | No |
| Supporting protocol for BACnet | | No |
| Supporting protocol for other bus systems | | Yes |
| Number of HW-interfaces industrial Ethernet | | 0 |
| Number of interfaces PROFINET | | 0 |
| Number of HW-interfaces RS-232 | | 0 |
| Number of HW-interfaces RS-422 | | 0 |
| Number of HW-interfaces RS-485 | | 1 |
| Number of HW-interfaces serial TTY | | 0 |
| Number of HW-interfaces USB | | 0 |
| Number of HW-interfaces parallel | | 0 |
| Number of HW-interfaces other | | 0 |
| With optical interface | | No |
| With PC connection | | Yes |
| Integrated breaking resistance | | Yes |

| | | | |
|---|---|---|---|
| 4-quadrant operation possible | | | Yes |
| Type of converter | | | U converter |
| Degree of protection (IP) | | | IP66 |
| Degree of protection (NEMA) | | | 4X |
| Height | | mm | 257 |
| Width | | mm | 188 |
| Depth | | mm | 239.3 |


© 04/2023 by Eaton Industries GmbH