PRODUCT-DETAILS

SPL16/25M

16MM GS-PVC COAT CONDUIT 25M - BL



General Information

Extended Product Type:	SPL16/25M
Product ID:	7TCA296030R0078
EAN:	5020963000560
Catalog Description:	16MM GS-PVC COAT CONDUIT 25M - BL
Long Description:	Liquid Tight, Oil Resistant, Medium Flexiblility Conduit, Nominal Conduit Size 16mm, Outside Diameter 17.8mm, Inside Diameter 12.5mm, Static Bend Radius 50mm, Reel Length 25 Meters, PVC Covering with Galvanised Steel Core, Black
Display Name:	SPL16/25M

Additional Information

Product Main Type:	Adaptaflex Flexible Cable Protection
Application:	Liquid Tight - Indoors / Outdoors, Marine, Buildings

Ordering

EAN:	5020963000560

© 2026 ABB. All rights reserved.

UPC:	786210239392

Dimensions

Outside Diameter:	17.8 mm

Technical

Number of Batteries:	0
Color:	Black
Material:	Galvanized Steel Core with PVC Covering

Environmental

WEEE Category:	Product Not in WEEE Scope
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	5020963000560
Package Level 1 Height:	6 in 152 mm
Package Level 1 Depth / Length:	16 in 406 mm
Package Level 1 Width:	16 in 406 mm

Certificates and Declarations

Declaration of Conformity - CE:	9AKK107492A9618
RoHS Declaration:	9AKK107992A8994
REACH Declaration:	9AKK107992A8994

External Classifications and Standards

ETIM 8:	EC001179 - Protective metallic hose
ETIM 9:	EC001179 - Protective metallic hose
UNSPSC:	39131706

Categories

© 2026 ABB. All rights reserved.

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems



© 2026 ABB. All rights reserved.