Brand of NTN corporation

Technical data

UKPA210H

Bearing units




Grey cast housing, radial insert ball bearing with adapter sleeve,seal with slinger

KIT CONTENT

UK210G2H, PA210

VISUAL (S)



PRODUCT DEFINITION

Brand	SNR
A - Housing width	60 mm
A1 - Housing top width	32 mm
B - Width of Inner Ring	31 mm
d - Shaft diameter	45 mm
d1 - Outer dia of eccent. Lock. collar / nut of adapter sleeve	70 mm

UKPA210H
Bearing units

PRODUCT DEFINITION	
E - Mounting hole thread depth	25 mm
G - Grease fitting	M6x1
H - Distance mounting base to centerline spheric. seating diam.	57,2 mm
H1 - Housing foot height	14 mm
H2 - Housing height	116 mm
J - Mounting holes distance	94 mm
L - Housing length	130 mm
L1 - Housing foot length	35 mm
N - Mounting hole dimension	M16
s1 - Distance nut to middle of bearing raceway	27,5 mm

PRODUCT PERFORMANCE	
C - Dynamic load rating	35100000 mN
C0 - Static load rating	23200000 mN
Operating temperature min.	253,15 °K
Operating temperature max.	373,15 °K

OTHER FEATURES	
Mass	2,73 kg
Adapter sleeve designation	H2310