Specifications

Eaton 102419



Catalog Number: 102419

Eaton xEnergy Basic LV systems Low voltage switchgear. Metal door, for HxW=1760x400mm

General specifications

Product Name	**Catalog Number**
Eaton xEnergy Basic door	102419
EAN	**Product Length/Depth**
4015081023073	45 mm
Product Height	**Product Width**
1710 mm	415 mm
Product Weight	**Compliances**
6.2 kg	RoHS conform

Powering Business Worldwide

Product specifications

Used with

Accessory consideration
Service distribution board IVS
Accessory
Floor-standing enclosure

Special features

Closed
Single wing door
Mounting from front, fast mounting, hinges on left or right possible
Door opening angle 167°
3-point turn lock with roller lever lock

Type

Additional equipment for floor-standing service distribution board IVS

Features

EMC-version

Accessory/spare part type

Doors

Surface finishing

Powder coating
With powder coating

Color

Gray
Light gray (RAL 7035)

Degree of protection

IP30
NEMA Other

Unit type

Modular system

Suitable for height

1760 mm

Suitable for width

400 mm

Cover/door type

Three-point turn-lock

Resources

Brochures

eaton-xenergy-basic-light-brochure-br014024-en-us.pdf

Catalogs

eaton-distribution-boards-xenergy-basic-catalog-ca014010en-en-us.pdf

Declarations of conformity

DA-DC-03_Z-DS

Sales notes

eaton-f3a-flange-flyer-fl019005en-en-us.pdf

Material

Sheet steel

Steel

Housing material

Sheet steel

Model

Stop door

Mounting method

Flush mounting

Floor standing distribution board

Surface mounting

Functions

Floor-standing enclosure

Additional equipment

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia