PRODUCT-DETAILS

OS250B21LRP

OS250B21LRP SPECIAL CONNECTED SWITCH FUSE



General Information

Extended Product Type	OS250B21LRP
Product ID	1SCA022854R5850
EAN	6417019303888
Catalog Description	OS250B21LRP SPECIAL CONNECTED SWITCH FUSE
Long Description	Switch Fuses,Front Operated,3-pole,21 (Between the Poles),British Standard,B1-B3,Handle and shaft included.

ABB EcoSolutions

End of Life Instructions	1SCC311049M0201
Environmental Product Declaration - EPD	1SCC311197D0201
Group Waste to Landfill Target	UL 2799 Zero Waste To Landfill Validation available

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658

© 2024 ABB. All rights reserved.

REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311019M0006
Environmental Product Declaration - EPD	1SCC311197D0201
End of Life Instructions	1SCC311049M0201

Environmental

Pollution Degree	3

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Dimensions

Product Net Width	353 mm
Product Net Height	150 mm
Product Net Depth / Length	234 mm
Product Net Weight	5.27 kg 11.62 lb

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	215 mm 8.46 in
Package Level 1 Depth / Length	395 mm 15.55 in
Package Level 1 Height	215 mm 8.46 in
Package Level 1 Gross Weight	5.97 kg 13.16 lb
Package Level 1 EAN	6417019303888

Technical

Conventional Free-air Thermal Current (I_{th})	Θ = 40 °C 250 A
Conventional Thermal Current (I_{the})	Fully Enclosed 250 A
Fuse Size	B1-B3
Fuse System	British Standard
Handle Type	Pistol handle and shaft included
Mounting Type	Base mounting

© 2024 ABB. All rights reserved.

Number of Poles	3P
Operating Mode	Front Operated
Pollution Degree	3
Position of Line Terminals	Left In - Right Out
Power Loss	at Rated Operating Conditions per Pole 17 W
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Rated Current (I_n)	Main Circuit 250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Current AC-21A (I_e)	(500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 75 kW (400 V) 140 kW (415 V) 145 kW (500 V) 170 kW (690 V) 250 kW
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kiloampere rms
Standards	IEC 60947-3
Switches Operating Mechanism	21 (Between the Poles)
Terminal Type	Lug terminals
Terminal Width	25 mm
Tightening Torque	30 ... 44 N·m

Technical UL/CSA

Tightening Torque	30 ... 44 N·m

Certificates and Declarations

A2L Certificate - IEC	1SCC311209D0201
ATEX Certificate	No certification needed
CCC Certificate	CCC OS200-250_LR 2016
Declaration of Conformity - CE	1SCC311120D2702
DNV GL Certificate	1SCC311132D0201
UL Certificate	No certification needed

Classifications

Object Classification Code	Q
ETIM 8	EC001040 - Fuse switch disconnector
ETIM 9	EC001040 - Fuse switch disconnector
UNSPSC	39122233
IDEA Granular Category Code (IGCC)	5291 >> Fuse switch disconnector
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Switches → Switch Fuses



© 2024 ABB. All rights reserved.