Date: 22/04/2024

PCS2GA 8 … 40 bar 1/4 NPT-F, 1/2 -14 NPT-F

Compact Pressure Switch

Item number: 48778761

Quantity: 1 pcs.

Order code: PCS2GA-BAIC-1ASZZZZZZ ZCKW
B001800DZZZZZZZZ

Overview:
PCS2GA 8 … 40 bar 1/4 NPT-F, 1/2 -14 NPT-F
Compact Pressure Switch
PCS
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Hastelloy C276
Connection: Stainless steel AISI 316L
contact version: 1xSPDT, silver contact
Setting range, working range, proof pressure: 8 … 40 bar, working range 0 … 100 bar, proof pressure 400 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case

Ingress Protection: IP66
Brand: WIKA Instruments Italia
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range

1. set point: 18.00 bar decreasing,

Details:
Compact Pressure Switch
Model PCS
Specifications according to data sheet: PV 33.30
Repeatability of set point: ≤ 1% of end of setting range
switch enclosure: aluminium,copper-free
Measuring elements and wetted parts: Diaphragm Hastelloy C276
1xSPDT, silver contact
8 … 40 bar, working range 0 … 100 bar, proof pressure 400 bar
Process connection: 1/4 NPT-F
Electrical connection: 1/2 -14 NPT-F
standard direct or wall mounting, fixing bore on the case
Approvals / Certificates: without
Switch standard: without
Brand: WIKA Instruments Italia
Ingress Protection: IP66
PCS2GA 8 … 40 bar
1. set point: 18.00 bar decreasing,

© 2024 - WIKA Instruments s.a.r.l.