
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
E	ECN 7987: UPDATED NOTES TO MATCH SUPPLIER SPEC	6/16/15	D. CASTRO



△E **NOTES:**

MATERIAL:
CONNECTOR SHELL: STEEL
CONNECTOR INSULATOR: THERMOPLASTIC, UL94V-0 RATED
CONTACTS: BRASS

FINISH:
FRONT SHELL: NICKEL PLATED
BACK SHELL: TIN PLATED
CONTACTS: 5 µin SELECTIVE GOLD
SOLDER CUPS: TIN PLATED

ELECTRICAL:
DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC rms
INSULATION RESISTANCE: 500MΩ @ DC 500V
CONTACT RESISTANCE: 25 MILLIOHMS MAX
CURRENT RATING: 1 AMP

MISCELLANEOUS:
OPERATING TEMPERATURE: -55°C TO +105°C
CONNECTOR SHALL BE PACKAGED IN ACCORDANCE WITH L-COM SPEC PS-0031.

REGULATORY COMPLIANCE:
CE2011/65/EU(RoHS DIRECTIVE)

CATALOG #	PACKAGING
SD15S	1/BAG
SD15S-TRAY	70/TRAY

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES [mm]
OVERALL CABLE LENGTH TOLERANCE:
≤12 [305] = +1 [25] / -0
>12 [305] ≤60 [1524] = +2 [51] / -0
>60 [1524] ≤120 [3048] = +4 [102] / -0
>120 [3048] ≤300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0%
ALL OTHER DIMENSIONAL TOLERANCES:
.X = ± .2
.XX = ± .02
.XXX = ±.005
PROJECTION

APPROVALS	DATE
DRAWN BY B.MAZEJKA	11/10/2003
CHECKED BY C.McCORMICK	12/08/2003
APPROVED BY D.PARHAM	12/08/2003

CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY

COLOR VARIATIONS MAY OCCUR

1AC02-012

L-COM Global Connectivity
45 BEECHWOOD DRIVE
NORTH ANDOVER, MA
01845

CATEGORY
D-SUBMINIATURE

PRODUCT DESCRIPTION
DB15F SOLDER CUP CONNECTOR

SIZE	FSCM NO.	DWG. NO.	REV.
A	43321	SD15S	E

SCALE: NONE | CAD FILE: SD15S.SLDDRW | SHEET 1 OF 1