PRODUCT-DETAILS

E2.2S 2000 Ekip Hi-Touch LSIG 4p F HR

E2.2S 2000 Ekip Hi-Touch LSIG 4p F HR



General Information

Extended Product Type	E2.2S 2000 Ekip Hi-Touch LSIG 4p F HR
Product ID	1SDA071679R1
EAN	8015644755294
Catalog Description	E2.2S 2000 Ekip Hi-Touch LSIG 4p F HR
Long Description	C.BREAKER SACE EMAX2 E2.2S 2000 FIXED FOUR-POLE WITH TERMINALS REAR HORIZONTAL AND SOLID-STATE RELEASE IN AC EKIP/HI-TOUCH-LSIG R 2000 FITTED WITH: 4 AUXILIARY CONTACT AND C.BREAKER IN POSITION OPEN-CLOSED

ABB EcoSolutions

ABB EcoSolutions	Yes
Environmental Product Declaration - EPD	9AKK108468A1902 9AKK108468A1909

Material Compliance

REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

© 2024 ABB. All rights reserved.

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Toxic Substances Control Act - TSCA	9AKK108467A8326
SCIP	2fd6aa24-af89-4805-bf6d-2dc199d47f86 Italy (IT)
Simplified SCIP	bd6e3f4b-d2e2-462c-9e88-fd9fc55d6bbd Germany (DE) e851b46b-b8a4-4cc0-8ae3-f9764fa5362d Hungary (HU) 47bf89e0-6899-44d5-a18d-1ee7c13ee619 Belgium (BE) ed414856-0b99-4d93-be65-62142653fa4f Spain (ES) 898b3e8e-fae7-4056-9342-16b3556d7e2d Hungary (HU) 8d64f960-3831-48aa-ab9e-bcea97daaa8b Norway (NO) 7e3ebd7f-f3d5-4271-b543-6920349ddb8e Poland (PL) 36f1ccd8-13e4-4998-b647-9c897a349563 France (FR) 10337001-99d9-4e9c-9202-52423418a4c6 Germany (DE) 2e35534c-e04b-4c2a-8d11-0d8f3f1c06a7 Germany (DE) 02c0463b-a204-4a45-9e2c-bea1844e5528 Croatia (HR) 8d247a88-6b1d-40ae-99ca-9d6719e62700 Bulgaria (BG) d76aeb6e-cbdd-44c8-a18d-ced0261f758b Denmark (DK) d56e797b-1f0f-4320-a431-545fab382558 Germany (DE) aea4a51a-6350-4029-b29c-ad4d93e69748 Germany (DE) 42910272-0f78-4ff2-9e16-3bff30af97f7 Finland (FI) 4b1faf69-52a8-451e-bb5d-792f2548e0dd Greece (GR) 6117abcd-cfc7-4ac3-8c7c-1aa5d9a1043e France (FR) 98ba0f2b-8989-487b-9b2a-1369ca699a22 Sweden (SE) 580cca63-b3b3-484d-bcbe-0cd0e081662b Belgium (BE) a8970d8c-07b7-4843-aa13-e97bba896e93 Netherlands (NL) fc1f8138-7364-489a-b441-75be51e820bf Estonia (EE) 2d396dce-7a81-4598-835d-39cbb5fc9043 Poland (PL) cd21be63-1a2b-4ae0-a5b8-1a766016261e Poland (PL) e680c7c3-b997-4012-ab81-14424d91bed5 Czech Republic (CZ) 77049f79-f334-4543-8ae1-accc41eba450 Sweden (SE) d581ac82-d3c4-4c38-b552-33ed9ec69fb9 Portugal (PT)

Environmental

Environmental Information	9AKK108467A6707

Ordering

Order Code US and Canada	ZBSTEKBK200A000000XX
EAN	8015644755294
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensions

Product Net Width	366 mm
Product Net Height	371 mm
Product Net Depth / Length	270 mm
Product Net Weight	53 kg

Container Information

Package Level 1 Units	box 1 piece

© 2024 ABB. All rights reserved.

Package Level 1 Width	515 mm
Package Level 1 Height	610 mm
Package Level 1 Depth / Length	615 mm
Package Level 1 Gross Weight	58 kg
Package Level 1 EAN	8015644755294

Additional Information

Product Main Type	SACE Emax 2
Product Name	Air Circuit Breaker
Product Type	Air Circuit Breaker
Version	F
CAD Dimensional Drawing	1SDH001252R0123

Technical

Current Type	AC
Electrical Durability	Ue =< 440 V 10000 cycle Ue = 500 ... 690 V 8000 cycle 30 cycles per hour
Mechanical Durability	25000 cycle 60 cycles per hour
Neutral Pole Current ([% Iu])	100 %
Number of Poles	4P
Power Loss	212 W
Rated Current (I_n)	2000 A
Rated Impulse Withstand Voltage (U_{imp})	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i)	AC 1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Service Short-Circuit Breaking Capacity, in % of Icu (I_{cs})	100 %
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I_u)	2000 A

© 2024 ABB. All rights reserved.

Rated Voltage (U_r)	690 V
Recommended Screw Driver	Main Circuit M12
Release	Ekip Hi-Touch LSIG
Release Type	EL
Short-Circuit Performance Level	S
Standards	IEC
Sub-type	E2.2
Suitable for IT Networks	Yes, 690V
Terminal Connection Type	Rear flat Horizontal
Terminal Type	Bolt
Tightening Torque	70 N·m

Certificates and Declarations

ATEX Certificate	No certification needed
CSA Certificate	No certification needed
CSA Certificate (Intrinsic Safe)	No certification needed
Data Sheet, Technical Information	1SDC200023D0209
Declaration of Conformity - CE	9AKK106713A5902
UL Certificate	No certification needed
VDE Certificate	No certification needed
Mechanical Drawings	1SDH001000R0100
Wiring Diagram	1SDM000091R0001
Instructions and Manuals	1SDH001000R0002
Instructions and Manuals (Part 2)	1SDH001316R1002

Classifications

ETIM 8	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 9	EC000228 - Power circuit-breaker for trafo/generator/installation protection
IDEA Granular Category Code (IGCC)	4926 >> Air circuit breakers
Object Classification Code	Q
UNSPSC	39121615
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.1 : 27370409

© 2024 ABB. All rights reserved.

Categories

Low Voltage Products and Systems → Circuit Breakers → Air Circuit Breakers → Emax 2



© 2024 ABB. All rights reserved.