Specification
PC15250 Mk2
Phase Sequence Indicator





Electrical
Input voltage range: 50V to 600V AC (Phase to Phase)
Input frequency: 40 to 60Hz
Input current: < 3mA

Environmental
Temperature (Operating & Storage): -10°C to 55°C
Humidity (Operating & Storage): ≤ 85% R.H
Altitude: up to 2000m
Pollution Degree: 2

General
Power: from circuit under test
Fuses: 600V 0.5A 50kA HRC rated fuses (6x32mm) x 3, one in each probe
Dimensions: 116(L) x 69(W) x 25(D) mm
Weight packed: 361g approx
Includes: instructions

Safety
Conforms to GS38 & BS EN61557-7, CAT IV 600V
Class II, Double Insulation

EMC
Conforms to BS EN61326-2-2

Check out what else you can get from Martindale:

- 17th Edition Testers
- Accessories
- Calibration Equipment
- Continuity Testers
- Electricians' Kits
- Environmental Products
- Full Calibration & Repair Service
- Fuse Finders
- Digital Clamp Meters
- Digital Multimeters
- Labels
- Microwave Leakage Detectors
- Motor Maintenance Equipment
- Multifunction Testers
- Non-trip Loop Testers
- Pat Testers & Accessories
- Phase Rotation Testers
- Proving Units
- Socket Testers
- Thermometers & Probes
- Test Leads
- Voltage Indicators
- Specialist Metrohm Testers (4 & 5kV)
- Specialist Drummond Testers

Martindale Electric Company Limited
Metrohm House, Penfold Trading Estate, Imperial Way, Watford WD24 4YY, UK
Tel: +44(0)1923 441717 Fax: +44 (0)1923 446900
E-mail: sales@martindale-electric.co.uk
Website: www.martindale-electric.co.uk

© 2013 Martindale Electric Company Ltd.
Registered in England No. 3387451. E. & O.E. Document Rev3 LITPC15250