Rittal – The System.

Faster – better – everywhere.

Slide rail, 1 U, depth-variable for VX IT, TE – DK 5501.460

Date : Oct 26, 2021

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Slide rail, 1 U, depth-variable for VX IT, TE – DK 5501.460

created: 26.10.2021 on www.rittal.com/com-en



Product description

Benefits:	Tool-free, time-saving one-man assembly from the enclosure front All three mounting holes in the EIA system punchings are available for screw-fastening the equipment. Alternatively, direct screw fastening in the TE 8000 to the 482.6 mm (19") system punchings is also possible
Applications:	For mounting on the front mounting level To support heavy installed equipment To adapt to individual distances between 482.6 mm (19") levels
Material:	Sheet steel
Surface finish:	Zinc-plated
Supply includes:	Assembly parts
Note:	Effective contact surface 25 mm per side

Product description

To fit:	Enclosure type: VX IT Enclosure type: TS IT Enclosure type: TE
Installation options:	482.6 mm (19") L mounting angles, front and rear 482.6 mm (19") mounting frames front and rear for 482.6 mm (19") mounting angles, standard
Distance between	min.: 400 mm

levels:	max.: 600 mm
Contact surface:	Width: 25 mm
Load capacity:	800 N
Packs of:	2 pc(s).
Weight/pack:	2.36 kg
Copper weight (kg per piece):	0
EAN:	4028177679016
Customs tariff number:	73269098
ETIM 7.0:	EC002620
ETIM 6.0:	EC002620
eCl@ss 8.0/8.1:	27189261
eCl@ss 6.0/6.1:	27182590
Product description:	DK Slide rail, support surface width: 25 mm, depth-variable, 80 kg, For two 482.6 mm (19")-mounting angles (front+rear), distance between levels:: 400-600 mm

Approvals

Certificates:	NA